

MODEL : RS-35-48

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 200 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 14 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 42 V- 54 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	39.66V~55.41 V/ 230VAC 3966V~ 55.41 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 1 %~ -1 % (Max)	I/P: 88 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.1 %~ -0.1 %	P
4	LINE REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 88VAC ~ 264VAC O/P:FULL LOAD Ta:25°C	V1: 0.1 %~ -0.1 %	P
5	LOAD REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.1 %~ -0.1 %	P
6	SET UP TIME	230VAC/ 500 ms (Max) 115VAC/ 1200 ms (Max)	I/P: 230VAC I/P: 230VAC O/P:FULL LOAD Ta:25°C	230VAC/ 365 ms 115VAC/ 365 ms	P
7	RISE TIME	230VAC/ 50ms (Max) 115VAC/ 50ms (Max)	I/P: 230VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 19 ms 115VAC/ 20 ms	P
8	HOLD UP TIME	230VAC/ 80 ms (TYP) 115VAC/ 15 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 94 ms 115VAC/ 21 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 4800 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	177 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	88VAC~264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	58 V~ 264 V	P
			I/P: LOW-LINE-3V= 85 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47 HZ ~ 63 HZ NO DAMAGE OSC	I/P: 88VAC ~ 264VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	88.5 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	88.5 %	P
4	INPUT CURRENT	230V/ 0.55 A(TYP) 115V/ 0.8 A(TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.44 A/ 230 VAC I = 0.68 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 36 A(TYP) COLD START	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I = 29 A/ 230 VAC	P
6	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P: 254 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.32 mA N-FG: 0.32 mA	P
7	No load power consumption	<0.5W	I/P: 230VAC O/P:NO LOAD Ta:25°C	0.465W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 %~ 150 %	I/P: 230 VAC I/P: 115 VAC O/P: TESTING Ta:25°C	131 %/ 230 VAC 127 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1:55.2 V~ 64.8 V	I/P: 230 VAC I/P: 115 VAC O/P: MIN LOAD Ta:25°C	62.4 V/ 230 VAC 62.4 V/ 115 VAC Hiccup Model	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : RS-35-24 1. ROOM AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: FULL LOAD Ta= 27.4 °C 2. HIGH AMBIENT BURN-IN : 3 HRS I/P: 230 VAC O/P: FULL LOAD Ta= 50 °C			P																																																												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= °C</th> <th>HIGH AMBIENT Ta= °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>LF1</td> <td>TF-484</td> <td>48.8°C</td> <td>68.0°C</td> </tr> <tr> <td>2</td> <td>C57</td> <td>330U/35V NCC 105°C KY</td> <td>48.2°C</td> <td>68.4°C</td> </tr> <tr> <td>3</td> <td>BD1</td> <td>KBP208G 2A/800V LT</td> <td>50.0°C</td> <td>70.1°C</td> </tr> <tr> <td>4</td> <td>C5</td> <td>82U/400V HU4 105°C</td> <td>42.0°C</td> <td>62.4°C</td> </tr> <tr> <td>5</td> <td>T1 CORE</td> <td>TF-1001 LS</td> <td>61.5°C</td> <td>80.2°C</td> </tr> <tr> <td>6</td> <td>T1 COIL</td> <td>TF-1001 LS</td> <td>69.8°C</td> <td>88.9°C</td> </tr> <tr> <td>7</td> <td>D55</td> <td>BYQ28X-200 10A/200V PH</td> <td>52.5°C</td> <td>71.8°C</td> </tr> <tr> <td>8</td> <td>U1</td> <td>1203</td> <td>56.1°C</td> <td>75.4°C</td> </tr> <tr> <td>9</td> <td>C10</td> <td>100U/35V RUB 105°C YXF</td> <td>55.1°C</td> <td>73.5°C</td> </tr> <tr> <td>10</td> <td>D1</td> <td>HER306 3A/600V REC</td> <td>58.7°C</td> <td>79.3°C</td> </tr> <tr> <td>11</td> <td>Q1</td> <td>K2545 6A/600V TOS</td> <td>50.0°C</td> <td>69.6°C</td> </tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= °C	HIGH AMBIENT Ta= °C	1	LF1	TF-484	48.8°C	68.0°C	2	C57	330U/35V NCC 105°C KY	48.2°C	68.4°C	3	BD1	KBP208G 2A/800V LT	50.0°C	70.1°C	4	C5	82U/400V HU4 105°C	42.0°C	62.4°C	5	T1 CORE	TF-1001 LS	61.5°C	80.2°C	6	T1 COIL	TF-1001 LS	69.8°C	88.9°C	7	D55	BYQ28X-200 10A/200V PH	52.5°C	71.8°C	8	U1	1203	56.1°C	75.4°C	9	C10	100U/35V RUB 105°C YXF	55.1°C	73.5°C	10	D1	HER306 3A/600V REC	58.7°C	79.3°C	11	Q1	K2545 6A/600V TOS	50.0°C	69.6°C		
NO	Position	P/N	ROOM AMBIENT Ta= °C	HIGH AMBIENT Ta= °C																																																													
1	LF1	TF-484	48.8°C	68.0°C																																																													
2	C57	330U/35V NCC 105°C KY	48.2°C	68.4°C																																																													
3	BD1	KBP208G 2A/800V LT	50.0°C	70.1°C																																																													
4	C5	82U/400V HU4 105°C	42.0°C	62.4°C																																																													
5	T1 CORE	TF-1001 LS	61.5°C	80.2°C																																																													
6	T1 COIL	TF-1001 LS	69.8°C	88.9°C																																																													
7	D55	BYQ28X-200 10A/200V PH	52.5°C	71.8°C																																																													
8	U1	1203	56.1°C	75.4°C																																																													
9	C10	100U/35V RUB 105°C YXF	55.1°C	73.5°C																																																													
10	D1	HER306 3A/600V REC	58.7°C	79.3°C																																																													
11	Q1	K2545 6A/600V TOS	50.0°C	69.6°C																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 133 % LOAD Ta:25°C	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100 % LOAD Ta= -25 °C	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-50°C)	I/P:230 VAC O/P:FULL LOAD	± 0.01 %(0-50°C)	P																																																												
6	VIBRATION TEST	1 Set Operating at I/P: 230 VAC NO LOAD (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:5G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																												

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 2.64 mA I/P-FG: 2.51 mA O/P-FG: 1.47 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 1G Ω I/P-FG: 2G Ω O/P-FG: 2G Ω NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C	6 mΩ	P
4	APPROVAL	TUV: Certificate NO : R50046884 UL: File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				



M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C 57 IS THE MOST CRITICAL COMPONENT I/P: 230 VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 512858 HRS I/P: 230 VAC O/P:FULL LOAD Ta= 50 °C LIFE TIME= 107060 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 249K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDCT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated K2545 : 600 V 6 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 416 V (2) 400 V (3) 550 V	P
2	Diode Peak Voltage	D 55 Rated F10LC40 : 400V 10 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 318 V (2) 382 V (3) 312 V	P
3	Clamp Diode Peak Voltage	D1 Rated HER306 : 600 V 3 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 450 V (2) 450 V	P
4	Input Capacitor Voltage	C 5 Rated : 82 u 400 V 105 °C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 386 V (2) 376 V (3) 376 V	P
5	Control IC Voltage Test	U 1 Rated 1203 : 16 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 12.8 V (2) 12.7 V (3) 12.4 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2004/4/29	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2004/8/2	PRODUCT SAMPLE A405B06	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023