



Test Report: LRS-35-24

35W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test


■ RELIABILITY TEST

ENVIRONMENT TEST


DESIGN VERIFY TEST

OUTPUT FUNCTION TEST


| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|----------------------------------|---|--|--|
| 1 | OUTPUT VOLTAGE ADJUST RANGE | CH1: 21.6V~ 28.8 V | I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C | 20.54V~30.36V/230VAC 20.54V~30.36V/115VAC |
| 2 | OUTPUT VOLTAGE(Max) TOLERANCE | V1: 1 %~ -1 % | I/P: 100VAC /264VAC O/P:FULL/ MIN. LOAD Ta:25°C | V1: -0.025 %~ 0.025% |
| 3 | LINE REGULATION (Max) | V1: 0.5 %~ -0.5 % | I/P: 100VAC~ 264VAC O/P:FULL LOAD Ta:25°C | V1: 0%~ 0.025 % |
| 4 | LOAD REGULATION(Max) | V1: 0.5 %~ -0.5 % | I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25°C | V1: -0.025%~ 0 % |
| 5 | OVER/UNDERSHOOT TEST | < ±5% | I/P: 230VAC O/P:FULL LOAD Ta:25°C | < ±5% |
| 6 | RIPPLE & NOISE(Max) | V1: 150mVp-p | I/P:230VAC O/P:FULL LOAD Ta:25°C | V1: 28.4mVp-p |
| | | <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>high frequency :</p> <p>Ch1 Pk-Pk 27.0mV</p> </div> <div style="text-align: center;"> <p>low frequency :</p> <p>Ch1 Pk-Pk 28.4mV</p> </div> </div> | | |
| 7 | SET UP TIME(Max) | 230VAC/1000ms 115VAC/2000ms | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 400ms 115VAC/ 608ms |
| | | <p>INPUT=230VAC/50HZ @ FULL LOAD INPUT=115VAC/60HZ @ FULL LOAD</p> <p>CH1 : Output Voltage CH2 : AC Input Voltage CH1 : Output Voltage CH2 : AC Input Voltage</p> | | |




| | | | | |
|---|-----------------|-------------|---|----------------|
| 8 | RISE TIME (Max) | 230VAC/30ms | I/P : 230 VAC | 230VAC/25.8ms |
| | | 115VAC/30ms | I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 115VAC/ 25.2ms |




| | | | | |
|---|---------------------|-------------|---|----------------|
| 9 | HOLD UP TIME (Typ.) | 230VAC/30ms | I/P : 230 VAC | 230VAC/36.8ms |
| | | 115VAC/12ms | I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 115VAC/ 17.6ms |






INPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|-----------------------|----------------------------|--|--------------------------------------|
| 1 | INPUT VOLTAGE RANGE | 85VAC~264VAC | I/P:TESTING O/P:FULL LOAD Ta:25°C | 63V~264V |
| | | | I/P: (1)LOW-LINE-3V=82 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE) | TEST:OK |
| 2 | INPUT FREQUENCY RANGE | 47HZ ~63 HZ NO DAMAGE | I/P:100 VAC ~264 VAC O/P:FULL~MIN LOAD Ta:25°C | TEST: OK |
| 3 | INPUT CURRENT (Typ.) | 230V/ 0.42A 115V/ 0.70A | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | I=0.347A/ 230VAC I=0.576A/ 115VAC |
| 4 | LEAKAGE CURRENT | <0.75 mA / 240 VAC | I/P : 240 VAC O/P : Min LOAD Ta : 25°C | L-FG : 0.518 mA N-FG : 0.518 mA |
| 5 | NO LOAD CONSUMPTION | < 0.2W | I/P : 115VAC I/P : 230VAC O/P : NO LOAD Ta : 25°C | < 0.0795 W < 0.0686 W |
| 6 | EFFICIENCY(Typ.) | 88% | I/P:230 VAC O/P:FULL LOAD Ta:25°C | 88.39% |



| | | | | |
|---|----------------------|------------------------|---|-----------------|
| 7 | INRUSH CURRENT(Typ.) | 230V/40A COLD START | I/P : 230 VAC O/P : FULL LOAD Ta : 25°C | I=23.8A/ 230VAC |
|---|----------------------|------------------------|---|-----------------|



PROTECTION FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|-------------------------|--|--|---|
| 1 | OVER LOAD PROTECTION | 110 %~ 150 % | I/P: 264VAC I/P: 230VAC I/P: 100VAC O/P: TESTING Ta:25°C | 131.33%/ 264VAC 129.33%/ 230VAC 128.67%/100VAC PROTECTION TYPE : Hiccup mode, recovers automatically after fault condition is removed |
| 2 | OVER VOLTAGE PROTECTION | 28.8V~33.6 V | I/P: 264VAC I/P: 230VAC I/P: 85VAC O/P: MIN LOAD Ta:25°C | 31.5V/ 264VAC 31.5V/ 230VAC 31.5V/ 85VAC PROTECTION TYPE : Shut down o/p voltage, re-power on to recover |
| 3 | SHORT PROTECTION | SHORT EVERY OUTPUT 1 HOUR NO DAMAGE | I/P: 264VAC I/P: 85VAC O/P: FULL LOAD Ta:25°C | NO DAMAGE PROTECTION TYPE : Hiccup mode, recovers automatically after fault condition is removed |

COMPONENT STRESS TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|--|--|--|---|
| 1 | PWM Transistor (D to S) or (C to E) Peak Voltage | Q 1 Rated 6A/ 600 V | I/P:High-Line +3V =267V AC ON/OFF VDS: O/P: (1)Full Load (2)Output Short (3)Full load continue Ta:25°C | VDS: (1) 510V (2) 414V (3) 510V |
| 2 | Diode Peak Voltage | Q100 Rated 10A/200 V | I/P:High-Line +3V =267 V AC ON/OFF O/P: (1)Full Load (2)Output Short (3)Full load continue Ta:25°C | Q100: VDS: (1) 118V (2) 94.8V (3) 116V |
| 3 | Input Capacitor Voltage | C5 Rated: :68 μ / 400 V 105 °C | I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2) Min load input on /Off (3)Full Load /Min load Change Ta:25°C | (1) 376V (2)370 V (3) 372V |
| 4 | Control IC Voltage Test | PWM IC U1 Rated 10.8 V~30V | I/P:High-Line +3V =267 V AC ON/OFF O/P(1)FULL LOAD (2) Output Short (3)O.L.P (4)O.V.P. (5)NO LOAD VR Min. LOW LINE Ta:25°C | (1) 17.0V (2) 15.0V (3) 15.0V (4) 20.8V (5) 14.9V |
| 5 | Clamp Diode Peak Voltage | D5 Rated : 3A/600V | I/P : High-Line +3V = 267 V AC ON/OFF O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C | (1) 462V (2) 464V |

SAFETY TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|----------------------|---|--|--|
| 1 | WITHSTAND VOLTAGE | I/P-O/P: 3.75KVAC/min I/P-FG :2KVAC/min O/P-FG:1.25KVAC/min | I/P-O/P: 4.125KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG:1.5 KVAC/min Ta:25°C | I/P-O/P:2.663mA I/P-FG:3.74mA O/P-FG:3.31m A NO DAMAGE |
| 2 | ISOLATION RESISTANCE | I/P-O/P:500VDC>100M Ω I/P-FG: 500VDC>100M Ω O/P-FG:500VDC>100M Ω | I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C | I/P-O/P: 9999M Ω I/P-FG: 9999M Ω O/P-FG: 9999M Ω NO DAMAGE |
| 3 | GROUNDING CONTINUITY | FG(PE) TO CHASSIS OR TRACE < 100 m Ω | 40A / 2min Ta:25°C | 21 m Ω |

E.M.C TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT |
|----|---|---|--|-------------------------------|
| 1 | HARMONIC | EN61000-3-2 CLASS A | I/P:230VAC/50HZ O/P:100%LOAD Ta:25°C | PASS |
| 2 | CONDUCTION | EN55022 CLASS B | I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C | PASS Test by certified Lab |
| 3 | RADIATION | EN55022 CLASS B | I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C | PASS Test by certified Lab |
| 4 | E.S.D | EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A |
| 5 | E.F.T | EN61000-4-4 INDUSTRY INPUT : 2KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A |
| 6 | SURGE | IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A |
| 7 | Test by certified Lab & Test Report Prepare | | | |

RELIABILITY TEST

ENVIRONMENT TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|------------------------|---|---|---|----|----------|--------------------------|------------------------|---|-----|--------|--------|---|-----|--------|--------|---|----|--------|--------|---|----|--------|---------|---|----|--------|--------|---|-----|--------|--------|---|--------|--------|--------|---|--------|--------|--------|---|------|--------|--------|----|------|--------|--------|----|------|--------|--------|----|------|--------|---------|----|----|--------|--------|----|-----|--------|--------|
| 1 | TEMPERATURE RISE TEST | MODEL : LRS-35-24 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=24.8°C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=50.1°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 24.8 °C</th> <th>HIGH AMBIENT Ta=50.1°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>43.8°C</td><td>68.3°C</td></tr> <tr><td>2</td><td>BD1</td><td>48.5°C</td><td>72.1°C</td></tr> <tr><td>3</td><td>C5</td><td>49.4°C</td><td>73.0°C</td></tr> <tr><td>4</td><td>D5</td><td>76.4°C</td><td>101.4°C</td></tr> <tr><td>5</td><td>Q1</td><td>69.5°C</td><td>90.8°C</td></tr> <tr><td>6</td><td>C35</td><td>52.2°C</td><td>75.1°C</td></tr> <tr><td>7</td><td>T1coil</td><td>58.5°C</td><td>79.7°C</td></tr> <tr><td>8</td><td>T1core</td><td>63.1°C</td><td>83.5°C</td></tr> <tr><td>9</td><td>C105</td><td>57.3°C</td><td>79.4°C</td></tr> <tr><td>10</td><td>C110</td><td>45.2°C</td><td>69.1°C</td></tr> <tr><td>11</td><td>L100</td><td>55.8°C</td><td>78.4°C</td></tr> <tr><td>12</td><td>Q100</td><td>80.7°C</td><td>103.6°C</td></tr> <tr><td>13</td><td>U1</td><td>51.5°C</td><td>75.5°C</td></tr> <tr><td>14</td><td>D30</td><td>51.3°C</td><td>74.9°C</td></tr> </tbody> </table> | NO | Position | ROOM AMBIENT Ta= 24.8 °C | HIGH AMBIENT Ta=50.1°C | 1 | LF1 | 43.8°C | 68.3°C | 2 | BD1 | 48.5°C | 72.1°C | 3 | C5 | 49.4°C | 73.0°C | 4 | D5 | 76.4°C | 101.4°C | 5 | Q1 | 69.5°C | 90.8°C | 6 | C35 | 52.2°C | 75.1°C | 7 | T1coil | 58.5°C | 79.7°C | 8 | T1core | 63.1°C | 83.5°C | 9 | C105 | 57.3°C | 79.4°C | 10 | C110 | 45.2°C | 69.1°C | 11 | L100 | 55.8°C | 78.4°C | 12 | Q100 | 80.7°C | 103.6°C | 13 | U1 | 51.5°C | 75.5°C | 14 | D30 | 51.3°C | 74.9°C |
| NO | Position | ROOM AMBIENT Ta= 24.8 °C | HIGH AMBIENT Ta=50.1°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | LF1 | 43.8°C | 68.3°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | BD1 | 48.5°C | 72.1°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | C5 | 49.4°C | 73.0°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | D5 | 76.4°C | 101.4°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | Q1 | 69.5°C | 90.8°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | C35 | 52.2°C | 75.1°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | T1coil | 58.5°C | 79.7°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | T1core | 63.1°C | 83.5°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | C105 | 57.3°C | 79.4°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | C110 | 45.2°C | 69.1°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 11 | L100 | 55.8°C | 78.4°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | Q100 | 80.7°C | 103.6°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 13 | U1 | 51.5°C | 75.5°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | D30 | 51.3°C | 74.9°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | OVER LOAD BURN-IN TEST | NO DAMAGE 1 HOUR (MIN) | I/P : 230 VAC O/P : 133% LOAD Ta : 25°C | TEST : OK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| | | | | |
|----|---|---|--|---|
| 3 | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 2 HOUR | I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -25 °C | TEST : OK |
| 4 | HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST | AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE | I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H | TEST : OK |
| 5 | TEMPERATURE COEFFICIENT | ± 0.03 %/°C (0~50°C) | I/P : 230 VAC O/P : FULL LOAD | ±0.003%/°C (0~50°C) |
| 6 | STORAGE TEMPERATURE TEST | 1. Thermal shock Temperature : -40°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC | | OK |
| 7 | THERMAL SHOCK TEST | 1. Thermal shock Temperature : -30°C~ 70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec | | OK |
| 8 | VIBRATION TEST | 1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C | | TEST : OK |
| 9 | CAPACITOR LIFE CYCLE | SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 50 °C LIFE TIME | | (1) 325342HRS (2) 71815HRS (3) 117394HRS (4) 139640HRS |
| 10 | MTBF | MIL-HDBK-217F TOTAL FAILURE RATE : 763.6KHRS | | |
| 11 | DMTBF/Accelerated Life Test | Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50°C | | |

| TEST RESULT | TESTER | APPROVAL |
|-------------|--------|----------|
| PASS | FRANK | WANGDZ |

2007/3/20 A50-S014