



Quality Engineering Test Report

MODEL : QP-375-5C 378 W

AC-DC QUAD OUTPUT SWITCHING POWER SUPPLY

V1 : +5 V/ 30 A V2 : +12 V/ 9 A

V3 : 15 V/ 4 A V4 : 15 V/ 4 A

(1) INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	<u>85 VAC</u> ~ <u>264 VAC</u> (Typ)	I/P: TESTING O/P: FULL LOAD Ta: 25°C	<u>60 V</u> ~ <u>264 V</u>	P
			I/P: LOW-LINE-3V= <u>82 V</u> HIGH-LINE+15%= <u>300 V</u> O/P: FULL/MIN LOAD ON: <u>1</u> Sec. OFF: <u>5</u> Sec. 300 TIMES (AC POWER ON/OFF)	TEST: <u>OK</u>	
2	INPUT FREQUENCY RANGE	<u>47 HZ</u> ~ <u>63 HZ</u> (Typ) NO DAMAGE OSC	I/P: <u>115 VAC</u> ~ <u>264 VAC</u> O/P: FULL-MIN LOAD Ta: 25°C	TEST: <u>OK</u>	P
3	INPUT CURRENT	<u>230V/ 3 A</u> (Max) <u>115V/ 6 A</u> (Max)	I/P: <u>230 VAC</u> O/P: FULL LOAD	I = <u>2.18 A/ 230 VAC</u> I = <u>4.43 A/ 115 VAC</u>	P
4	INRUSH CURRENT	<u>230 V/ 45 A</u> (Max) COLD START	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	I = <u>34 A/ 230 VAC</u>	P
5	LINE REGULATION	V1: <u>+0.5 %</u> ~ <u>-0.5 %</u> (Max) V2: <u>+0.5 %</u> ~ <u>-0.5 %</u> (Max) V3: <u>+0.5 %</u> ~ <u>-0.5 %</u> (Max) V4: <u>+0.5 %</u> ~ <u>-0.5 %</u> (Max)	I/P: <u>264 VAC</u> ~ <u>115 VAC</u> O/P: FULL LOAD Ta: 25°C	V1: <u>0 %</u> ~ <u>0 %</u> V2: <u>+0.05 %</u> ~ <u>-0.05 %</u> V3: <u>+0.04 %</u> ~ <u>-0.04 %</u> V4: <u>0 %</u> ~ <u>0 %</u>	P
6	EFFICIENCY	<u>77 %</u> (Typ)	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	<u>79 %</u>	P
7	POWER FACTOR	<u>230 V/ 0.95</u> (Typ) <u>115 V/ 0.98</u> (Typ)	I/P: <u>230 / 115 VAC</u> O/P: FULL LOAD Ta: 25°C	PF= <u>0.96 / 230 VAC</u> PF= <u>0.99 / 115 VAC</u>	P

(2) OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	SET UP TIME	<u>230 VAC/ 800 ms</u> (Max) ---- VAC/ ---- ms(Max)	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	<u>230VAC/ 144 ms</u> <u>115VAC/ 163 ms</u>	P
2	RISE TIME	<u>230VAC/ 50 ms</u> (Max) ---- VAC/ ---- ms(Max)	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	<u>230VAC/ 14 ms</u> <u>115VAC/ 15 ms</u>	P
3	HOLD UP TIME	<u>230VAC/ 20 ms</u> (Max) ---- VAC/ ---- ms(Max)	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	<u>230VAC/ 32 ms</u> <u>115VAC/ 31 ms</u>	P
4	OVER/UNDERSHOOT TEST	< <u>±5%</u> (Max)	I/P: <u>230 VAC</u> O/P: FULL LOAD Ta: 25°C	TEST: <u><5%</u>	P

5	OUTPUT VOLTAGE ADJUST RANGE	CH1: +10 %~ -5 % (TYP) CH2: +10 %~ -5 % (TYP) CH3: +10 %~ -5 % (TYP) CH4: +10 %~ -5 % (TYP)	I/P: <u>85</u> / ---- VAC O/P:MIN LOAD Ta:25°C	V1: <u>-12</u> %~ <u>+26</u> % V2: <u>-15</u> %~ <u>+15</u> % V3: <u>-16</u> %~ <u>+18</u> % V4: <u>-15</u> %~ <u>+16</u> %	P
			I/P: <u>85</u> VAC O/P:FULL LOAD (AC Turn ON/OFF in Vout Hi/Low Limit)	NO Damage	P
6	LOAD REGULATION	V1: <u>+0.8</u> %~ <u>-0.8</u> %(Max) V2: <u>+0.8</u> %~ <u>-0.8</u> %(Max) V3: <u>+0.8</u> %~ <u>-0.8</u> %(Max) V4: <u>+0.8</u> %~ <u>-0.8</u> %(Max)	I/P: <u>230</u> VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: <u>+0.1</u> %~ <u>-0.2</u> % V2: <u>+0</u> %~ <u>-0.05</u> % V3: <u>+0.08</u> %~ <u>-0.08</u> % V4: <u>+0.28</u> %~ <u>-0.28</u> %	P
7	OUTPUT VOLTAGE TOLERANCE	V1: <u>+1</u> %~ <u>-1</u> %(Max) V2: <u>+1</u> %~ <u>-1</u> %(Max) V3: <u>+1</u> %~ <u>-1</u> %(Max) V4: <u>+1</u> %~ <u>-1</u> %(Max)	I/P: <u>230</u> VAC ~ <u>115</u> VAC O/P:FULL/ <u>Min</u> % LOAD Ta:25°C	V1: <u>+0.23</u> %~ <u>-0.1</u> % V2: <u>+0.1</u> %~ <u>0</u> % V3: <u>+0.13</u> %~ <u>-0.1</u> % V4: <u>+0.1</u> %~ <u>-0.2</u> %	P
8	RIPPLE & NOISE	V1: <u>100</u> mVp-p (Typ) V2: <u>150</u> mVp-p (Typ) V3: <u>150</u> mVp-p (Typ) V4: <u>240</u> mVp-p (Typ)	I/P: <u>230</u> VAC O/P:FULL LOAD Ta:25°C	V1: <u>21</u> mVp-p V2: <u>10</u> mVp-p V3: <u>20</u> mVp-p V4: <u>13</u> mVp-p	P
9	DYNAMIC LOAD	CH1: <u>1000</u> mVp-p	I/P: <u>230</u> VAC O/P:FULL / Min LOAD 90% DUTY/1KHZ Ta:25°C	<u>332</u> mVp-p	P

(3) PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER VOLTAGE PROTECTION	CH1: <u>5.75</u> V~ <u>6.75</u> V(Typ)	I/P: <u>230</u> / <u>115</u> VAC O/P:MIN LOAD Ta:25°C	<u>6.6</u> V/ <u>230</u> VAC <u>6.6</u> V/ <u>115</u> VAC Shunt down -Repower ON	P
2	OVER LOAD PROTECTION	<u>105</u> %~ <u>135</u> %(Typ)	I/P: <u>230/115</u> VAC O/P:TESTING Ta:25°C	<u>115</u> %/ <u>230</u> VAC <u>114</u> %/ <u>115</u> VAC * Pulse by pulse	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: <u>264</u> VAC O/P: <u>100%</u> LOAD Ta:25°C	NO DAMAGE * Pulse by pulse	P
4	OVER TEMPERATURE PROTECTION	SPEC:Ta <u>80</u> °C.O.T.P. NO DAMAGE	I/P: <u>230</u> VAC O/P:FULL LOAD	<u>78</u> °C/ <u>230</u> VAC O.T.P. Active * Shunt down -Repower ON	P

(4) CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE SENSE	> <u>0.25 V</u>	I/P: <u>230 VAC</u> O/P:FULL LOAD Ta:25°C	> <u>0.5 V</u>	P
2	REMOTE CONTROL	<u>0 V~ 0.8V</u> POWER ON <u>4 V~ 10 V</u> POWER OFF	I/P: <u>230 VAC</u> O/P:FULL LOAD Ta:25°C	< <u>2.6 V</u> POWER ON > <u>2.6 V</u> POWER OFF	P
3	POWER GOOD SIGNAL	DELAY 10ms ~ 500ms	I/P: <u>230/115 VAC</u> O/P:FULL LOAD Ta:25°C	<u>61 ms/ 230VAC</u> <u>66 ms/ 115VAC</u>	P
4	POWER FAIL SIGNAL	> 1ms	I/P: <u>230/115 VAC</u> O/P:FULL LOAD Ta:25°C	<u>17 ms/ 230VAC</u> <u>17 ms/ 115VAC</u>	P

(5) SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: <u>3.0 KVAC/min</u> I/P-FG: <u>1.5 KVAC/min</u> O/P-FG: <u>0.5 KVAC/min</u>	I/P-O/P: <u>3.6 KVAC/min</u> I/P-FG: <u>1.8 KVAC/min</u> O/P-FG: <u>0.8 KVAC/min</u> Ta:25°C	I/P-O/P: <u>16 mA</u> I/P-FG: <u>8 mA</u> O/P-FG: <u>9 mA</u> NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC >100M ohms I/P-FG:500VDC >100M ohms O/P-FG:500VDC >100M ohms	I/P-O/P: <u>500 VDC</u> I/P-FG: <u>500 VDC</u> O/P-FG: <u>500 VDC</u> Ta:25°C	I/P-O/P: <u>5.4G ohms</u> I/P-FG: <u>4.99G ohms</u> O/P-FG: <u>3.8G ohms</u> NO DAMAGE	P
3	LEAKAGE CURRENT	< <u>2 mA</u> /240VAC	I/P:(<u>240VAC</u>)*1.06/ (60HZ) O/P:Min LOAD Ta:25°C	L-FG: <u>1.5 mA</u> N-FG: <u>1.5 mA</u>	P
4	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < <u>100 m ohms</u>	<u>30 A</u> / 2min Ta:25°C	<u>18 m ohms</u>	P
5	APPROVAL	TUV:Certificate NO:R50014021 UL:File No:E183223			

(6) E.M.C TEST

NO	TEST ITEM	TEST CONDITION	SPECIFICATION	RESULT	VERDICT
1	HARMONIC	IEC61000-3-2 *CLASS A	I/P: <u>230VAC/50HZ</u> O/P:FULL LOAD Ta:25°C	*PASS	P
2	CONDUCTION	EN55022 *CLASS A	I/P: <u>230VAC (50HZ)</u> O/P:FULL/50% LOAD Ta:25°C	*PASS Under Test by certified Lab	P
3	RADIATION	EN55022 *CLASS B	I/P: <u>230VAC (50HZ)</u> O/P:FULL/50% LOAD Ta:25°C	*PASS Under Test by certified Lab	P
4	E.S.D	IEC61000-4-2 *LIGHT INDUSTRY INDUSTRY AIR:8KV / Contac:4KV	I/P: <u>230VAC/50HZ</u> O/P:FULL LOAD Ta:25°C	* CRITERIA A CRITERIA B	P

5	E.F.T	IEC61000-4-4 *_LIGHT INDUSTRY INPUT:1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	*_CRITERIA A	P
6	SURGE	IEC61000-4-5 *_INDUSTRY L-N:2KV L,N-PE:4KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	*_CRITERIA A	P

7 Certificate By Interocean EMC Technology Corp Lab & Test Report Prepare

(7) ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																
1	TEMPERATURE RISE TEST T rise OF PARTS	MODEL:QP375-5A 1.ROOM AMBIENT BURN-IN: 2_HRS I/P: 230_VAC O/P: 100%_LOAD Ta= 24.4 °C 2.HIGH AMBIENT BURN-IN: 16_HRS I/P: 230_VAC O/P: 100%_LOAD Ta= 44.9 °C			P																																																																																
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>TEMP Ta= 24.4°C</th> <th>TEMP Ta= 44.9 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>D1</td><td>SMD 3A/600V</td><td>31.3</td><td>48.7</td></tr> <tr><td>2</td><td>D60</td><td>1N5406 3A/600V</td><td>63.0</td><td>82.5</td></tr> <tr><td>3</td><td>BD1</td><td>KBJ608G 6A/800V</td><td>36.6</td><td>54.6</td></tr> <tr><td>4</td><td>L1</td><td>TR-288</td><td>35.7</td><td>53.3</td></tr> <tr><td>5</td><td>U2</td><td>ML 4800CP</td><td>28.1</td><td>45.9</td></tr> <tr><td>6</td><td>Q1</td><td>IRFP460 20A/500V</td><td>46.4</td><td>66.1</td></tr> <tr><td>7</td><td>Q2</td><td>IRFR460 15A/500V</td><td>44.0</td><td>64.4</td></tr> <tr><td>8</td><td>D3</td><td>RHRP1560 15A/600V</td><td>58.6</td><td>79.3</td></tr> <tr><td>9</td><td>Q5</td><td>2SK2652 6A/900V</td><td>53.2</td><td>74.1</td></tr> <tr><td>10</td><td>Q4</td><td>2SK2652 6A/900V</td><td>63</td><td>84.1</td></tr> <tr><td>11</td><td>TRC1</td><td>BTA16-600B/6A</td><td>45.7</td><td>64.2</td></tr> <tr><td>12</td><td>TSW1</td><td>S7-22 80°C</td><td>46.1</td><td>65.8</td></tr> <tr><td>13</td><td>C5</td><td>470u/400V 85°C</td><td>36.0</td><td>53.2</td></tr> <tr><td>14</td><td>T1core</td><td>TF826</td><td>56.3</td><td>74.9</td></tr> <tr><td>15</td><td>T1coil</td><td>TF826</td><td>68.8</td><td>88.3</td></tr> </tbody> </table>	NO	Position	P/N	TEMP Ta= 24.4°C	TEMP Ta= 44.9 °C	1	D1	SMD 3A/600V	31.3	48.7	2	D60	1N5406 3A/600V	63.0	82.5	3	BD1	KBJ608G 6A/800V	36.6	54.6	4	L1	TR-288	35.7	53.3	5	U2	ML 4800CP	28.1	45.9	6	Q1	IRFP460 20A/500V	46.4	66.1	7	Q2	IRFR460 15A/500V	44.0	64.4	8	D3	RHRP1560 15A/600V	58.6	79.3	9	Q5	2SK2652 6A/900V	53.2	74.1	10	Q4	2SK2652 6A/900V	63	84.1	11	TRC1	BTA16-600B/6A	45.7	64.2	12	TSW1	S7-22 80°C	46.1	65.8	13	C5	470u/400V 85°C	36.0	53.2	14	T1core	TF826	56.3	74.9	15	T1coil	TF826	68.8	88.3	
NO	Position	P/N	TEMP Ta= 24.4°C	TEMP Ta= 44.9 °C																																																																																	
1	D1	SMD 3A/600V	31.3	48.7																																																																																	
2	D60	1N5406 3A/600V	63.0	82.5																																																																																	
3	BD1	KBJ608G 6A/800V	36.6	54.6																																																																																	
4	L1	TR-288	35.7	53.3																																																																																	
5	U2	ML 4800CP	28.1	45.9																																																																																	
6	Q1	IRFP460 20A/500V	46.4	66.1																																																																																	
7	Q2	IRFR460 15A/500V	44.0	64.4																																																																																	
8	D3	RHRP1560 15A/600V	58.6	79.3																																																																																	
9	Q5	2SK2652 6A/900V	53.2	74.1																																																																																	
10	Q4	2SK2652 6A/900V	63	84.1																																																																																	
11	TRC1	BTA16-600B/6A	45.7	64.2																																																																																	
12	TSW1	S7-22 80°C	46.1	65.8																																																																																	
13	C5	470u/400V 85°C	36.0	53.2																																																																																	
14	T1core	TF826	56.3	74.9																																																																																	
15	T1coil	TF826	68.8	88.3																																																																																	
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1.5 HOUR (MIN)	I/P: 230_VAC O/P: 114_% Ta:25°C	TEST: <u>OK</u>	P																																																																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR_	I/P: 230_VAC O/P: 100_%LOAD Ta= -11.5 °C	TEST: <u>OK</u>	P																																																																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55°C NO DAMAGE	I/P: 272_VAC O/P:FULL LOAD Ta= 55 °C HUMIDITY= 95 %R.H	TEST: <u>OK</u>	P																																																																																
5	TEMPERATURE COEFFICIENT	± 0.03_%(0-50°C)	I/P: 230_VAC O/P:FULL LOAD	± 0.01_%(0-50°C)	P																																																																																

(8) M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C <u>111</u> IS THE MOST CRITICAL COMPONENT I/P:230 VAC O/P:FULL LOAD Ta= <u>25</u> °C LIFE TIME= <u>224553</u> HRS I/P:230 VAC O/P:FULL LOAD Ta= <u>45</u> °C LIFE TIME= <u>61036</u> HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: <u>75931</u> HRS			P

(9) VIBRATION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	VIBRATION TEST	1 Carton & 1Set Operating at I/P:230VAC no load (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) Ta:25°C		TEST: ----	N/A

(10) COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q <u>5</u> Rated <u>2SK2850</u> : <u>900</u> V <u>6</u> A	I/P:High-Line +3V = <u>267</u> V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) <u>536</u> V (2) <u>800</u> V (3) <u>864</u> V	P
2	Diode Peak Voltage	D <u>102</u> Rated <u>S30SC4M</u> : <u>40</u> V <u>30</u> A	I/P:High-Line +3V = <u>267</u> V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) <u>17.2</u> V (2) <u>23.6</u> V (3) <u>25</u> V	P

DATE	SAMPLE	TEST RESULT	TEST	APPROVAL
2003/7/18	ENGINEERING SAMPLE	PASS	Vincent Tseng	Max Lin
2003/9/19	PRODUCTION SAMPLE A210A14	PASS	Vincent Tseng	Max Lin
2004/3/31	PRODUCTION SAMPLE A301B24	PASS	Vincent Tseng	Max Lin