

MODEL : RS-15-3.3

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1:80 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 31 mVp-p	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1:2.9V-3.6V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	2.62 V- 3.97 V/ 230 VAC 2.62 V- 3.97 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 3 %- -3% (Max)	I/P: 100 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.4 %- -0.4 %	P
4	LINE REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 100VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.1 %- -0.1 %	P
5	LOAD REGULATION	V1: 2 %- -2 % (Max)	I/P: 230 VAC O/P:FULL -MIN LOAD Ta:25°C	V1: 0.3 %- -0.3 %	P
6	SET UP TIME	230VAC: 1000 ms (Max) 115 VAC: 1000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 3 ms 115VAC/ 3 ms	P
7	RISE TIME	230VAC: 30 ms (Max) 115VAC: 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 1 ms 115VAC/ 2 ms	P
8	HOLD UP TIME	230VAC: 70 ms (TYP) 115VAC: 15 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 123 ms 115VAC/ 26 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 660 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	205 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	44 V~264V	P
			I/P: LOW-LINE-3V= 82 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 85 VAC ~ 264 VAC O/P:FULL -MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	72 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	73.42 %	P
4	INPUT CURRENT	230V/ 0.25 A (TYP) 115V/ 0.35 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.15 A/ 230 VAC I = 0.23 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 65 A (TYP) COLD START	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I = 60 A/ 230 VAC	P
6	LEAKAGE CURRENT	< 2 mA/ 240 VAC	I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.08 mA N-FG: 0.08 mA	P
7	No load power consumption	<0.5W	I/P: 230VAC O/P:NO LOAD Ta:25°C	0.233W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	173 %/ 230 VAC 143 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 3.8V~ 4.45V	O/P:DC SOURCE Ta:25°C	4.1 V/ 60mA Shut off o/p voltage ,clamping by zener diode	P
3	OVER TEMPERATURE PROTECTION	SPEC: U1 Tj140°C typically detect on main control IC NO DAMAGE	I/P: 230 VAC O/P:FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : RS-15-5			P																																																												
		1. ROOM AMBIENT BURN-IN : 2 HRS																																																															
		I/P: 230VAC O/P: FULL LOAD Ta= 28.8°C																																																															
		2. HIGH AMBIENT BURN-IN : 3 HRS																																																															
		I/P: 230VAC O/P: FULL LOAD Ta= 48.2°C																																																															
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 28.8 °C</th> <th>HIGH AMBIENT Ta= 48.2 °C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U1</td> <td>TNY279PN</td> <td>84.9°C</td> <td>106.8°C</td> </tr> <tr> <td>2</td> <td>D1</td> <td>FR107 1A/1KV</td> <td>76.6°C</td> <td>94.5°C</td> </tr> <tr> <td>3</td> <td>ZD1</td> <td>P6KE250A</td> <td>73.6°C</td> <td>91.4°C</td> </tr> <tr> <td>4</td> <td>C5</td> <td>33U/400V 105°C KMG</td> <td>59.8°C</td> <td>77.6°C</td> </tr> <tr> <td>5</td> <td>BD1</td> <td>KBP208G 2A/800V</td> <td>63.9°C</td> <td>81.4°C</td> </tr> <tr> <td>6</td> <td>LF1</td> <td>LF-510</td> <td>61.7°C</td> <td>80.2°C</td> </tr> <tr> <td>7</td> <td>T1 COIL</td> <td>TF-1641</td> <td>83.4°C</td> <td>101.6°C</td> </tr> <tr> <td>8</td> <td>C105</td> <td>1000U/16V 105°C ZLH</td> <td>67.2°C</td> <td>84.7°C</td> </tr> <tr> <td>9</td> <td>D100</td> <td>STPS30L60CT 30A/60V</td> <td>70.3°C</td> <td>88.6°C</td> </tr> <tr> <td>10</td> <td>L100</td> <td>DR011C</td> <td>58.6°C</td> <td>77.0°C</td> </tr> <tr> <td>11</td> <td>PCB</td> <td>TI 與 C105 間</td> <td>72.2°C</td> <td>90.4°C</td> </tr> </tbody> </table>				NO	Position	P/N	ROOM AMBIENT Ta= 28.8 °C	HIGH AMBIENT Ta= 48.2 °C	1	U1	TNY279PN	84.9°C	106.8°C	2	D1	FR107 1A/1KV	76.6°C	94.5°C	3	ZD1	P6KE250A	73.6°C	91.4°C	4	C5	33U/400V 105°C KMG	59.8°C	77.6°C	5	BD1	KBP208G 2A/800V	63.9°C	81.4°C	6	LF1	LF-510	61.7°C	80.2°C	7	T1 COIL	TF-1641	83.4°C	101.6°C	8	C105	1000U/16V 105°C ZLH	67.2°C	84.7°C	9	D100	STPS30L60CT 30A/60V	70.3°C	88.6°C	10	L100	DR011C	58.6°C	77.0°C	11	PCB	TI 與 C105 間	72.2°C	90.4°C
		NO	Position	P/N		ROOM AMBIENT Ta= 28.8 °C	HIGH AMBIENT Ta= 48.2 °C																																																										
		1	U1	TNY279PN		84.9°C	106.8°C																																																										
		2	D1	FR107 1A/1KV		76.6°C	94.5°C																																																										
		3	ZD1	P6KE250A		73.6°C	91.4°C																																																										
		4	C5	33U/400V 105°C KMG		59.8°C	77.6°C																																																										
		5	BD1	KBP208G 2A/800V		63.9°C	81.4°C																																																										
6	LF1	LF-510	61.7°C	80.2°C																																																													
7	T1 COIL	TF-1641	83.4°C	101.6°C																																																													
8	C105	1000U/16V 105°C ZLH	67.2°C	84.7°C																																																													
9	D100	STPS30L60CT 30A/60V	70.3°C	88.6°C																																																													
10	L100	DR011C	58.6°C	77.0°C																																																													
11	PCB	TI 與 C105 間	72.2°C	90.4°C																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 120 % LOAD Ta:25°C	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100% LOAD Ta= -20°C	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-50°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.01 %(0-50°C)	P																																																												
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:5G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																												

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 1.69 mA I/P-FG: 0.85 mA O/P-FG: 0.52 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C / 70%RH	I/P-O/P: 4 GΩ I/P-FG: 1.5 GΩ O/P-FG: 3 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C / 70%RH	7 mΩ	P
4	APPROVAL	TUV: Certificate NO : R 50111751 UL: File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	RS-15-5 : SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25°C LIFE TIME= 163780 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50°C LIFE TIME= 33067 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1608.8K HRS			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 50°C			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U1 Rated TNY279PN : 700V 1.2 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Output Short Ta:25°C	(1) 672 V (2) 664 V	P
2	Diode Peak Voltage	D100 Rated STPS30S45CT 30A/45V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2)Output Short Ta:25°C	(1) 24 V (2) 23 V	P
3	Clamp Diode Peak Voltage	D1 Rated FR107 1A/1KV	I/P:High-Line +3V = 267 V O/P: (1) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 628 V	P
4	Input Capacitor Voltage	C5 Rated 33u/400V 105°C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 382 V (2) 384 V (3) 384 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/6/1	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/7/6	PRODUCT SAMPLE W0706C14	PASS	VINCENT TSENG	MAX LIN
2007/8/30	PRODUCT SAMPLE W0708C17	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023