

MODEL : RT-50C

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 80 mVp-p (Max) V2: 120 mVp-p (Max) V3: 120 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 15 mVp-p (Max) V2: 16 mVp-p (Max) V3: 11 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 4.75 V-5.5 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	4.55V~ 5.8 V/230VAC 4.55V~ 5.8 V/115VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: -2%~ +2 % (Max) V2: -4%~ +8 % (Max) V3: -2%~ +2 % (Max)	I/P: 115 VAC / 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.14%~ -0.24 % V2: 2.01%~ -1.17 % V3: 0.09%~ 0 %	P
4	LINE REGULATION	V1: -0.5%~ +0.5 % (Max) V2: -1.5%~ +1.5 % (Max) V3: -0.5%~ +0.5 % (Max)	I/P: 115 VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0%~ 0 % V2: -0.08%~ 0.56 % V3: 0%~ 0 %	P
5	LOAD REGULATION	V1: -1%~ +1 % (Max) V2: -3%~ +3 % (Max) V3: -1%~ +1 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: -0.24%~ 0.12 % V2: 0.24%~ -0.12 % V3: -0.04%~ 0 %	P
6	CROSS REGULATION	V1: -1%~ +1 % (Max) V2: -3%~ +3 % (Max) V3: -1%~ +1 % (Max)	I/P: 230 VAC O/P: Testing O/P 60%LOAD Other O/P 40%LOAD Change Ta:25°C	V1: 0%~ 0 % V2: -0.93%~ 1.05 % V3: -0.04%~ 0 %	P
7	SET UP TIME	230 VAC/ 500 ms (Max) 115 VAC/ 1200 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 56 ms 115 VAC/ 56 ms	P
8	RISE TIME	230VAC/ 20ms (Max) 115VAC/ 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 11 ms 115 VAC/ 11 ms	P
9	HOLD UP TIME	230 VAC/ 50 ms (TYP) 115 VAC/ 10 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 67 ms 115 VAC/ 12 ms	P
10	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
11	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	80 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	88VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	70 V~ 264 V	P
			I/P: LOW-LINE-3V=85 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47 HZ ~63 HZ NO DAMAGE OSC	I/P: 88 VAC ~ 264 VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	78 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	79.44 %	P
4	INPUT CURRENT	230 V/ 0.8 A (TYP) 115 V/ 1.3 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.61 A/ 230 VAC I = 0.98 A/ 115 VAC	P
5	INRUSH CURRENT	230 V/36 A(TYP) COLD START	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I = 24 A/ 230 VAC	P
6	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P: 254 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.44 mA N-FG: 0.42 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 %- 150 %	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	121 %/230VAC 117 %/115VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 6.75 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	6.42 V/ 230 VAC 644 V/ 115 VAC Hiccup Model	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																
1	TEMPERATURE RISE TEST	MODEL : RT-50A 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 25.8 °C 2. HIGH AMBIENT BURN-IN : 60 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 36.6 °C			P																																																																																
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 25.8 °C</th> <th>HIGH AMBIENT Ta= 36.6 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TF-484 LS</td><td>59.2°C</td><td>68.2°C</td></tr> <tr><td>2</td><td>D56</td><td>SR360 3A/60V FMS</td><td>79.8°C</td><td>89.0°C</td></tr> <tr><td>3</td><td>BD1</td><td>D3SB60 4A/600V SHI</td><td>74.9°C</td><td>85.6°C</td></tr> <tr><td>4</td><td>C10</td><td>22U/50V NIPPON 105°C</td><td>55.5°C</td><td>65.7°C</td></tr> <tr><td>5</td><td>D50</td><td>F10SC6 10A/60V SHI</td><td>80.9°C</td><td>90.2°C</td></tr> <tr><td>6</td><td>Q1</td><td>K2628 6A/600V SYNYO</td><td>80.5°C</td><td>91.9°C</td></tr> <tr><td>7</td><td>D1</td><td>EGP20J 2A/600V ZOW</td><td>89.0°C</td><td>100°C</td></tr> <tr><td>8</td><td>C5</td><td>100U/400V RUB 105°C</td><td>52.3°C</td><td>62.7°C</td></tr> <tr><td>9</td><td>T1 COIL</td><td>TF-1017 LS</td><td>74.4°C</td><td>84.2°C</td></tr> <tr><td>10</td><td>D55</td><td>MBR1545CT 15A/45V ON</td><td>81.9°C</td><td>91.3°C</td></tr> <tr><td>11</td><td>T1 CORE</td><td>TF-1017 LS</td><td>68.4°C</td><td>78.6°C</td></tr> <tr><td>12</td><td>RG1</td><td>7905 1A/5V ON</td><td>74.2°C</td><td>84.1°C</td></tr> <tr><td>13</td><td>C56</td><td>2200U/16V RUB 105°C</td><td>71.8°C</td><td>80.8°C</td></tr> <tr><td>14</td><td>C53</td><td>1200U/16V RUB 105°C</td><td>65.8°C</td><td>74.8°C</td></tr> <tr><td>15</td><td>C51</td><td>470U/25V RUB 105°C YXG</td><td>67.9°C</td><td>77.0°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 25.8 °C	HIGH AMBIENT Ta= 36.6 °C	1	LF1	TF-484 LS	59.2°C	68.2°C	2	D56	SR360 3A/60V FMS	79.8°C	89.0°C	3	BD1	D3SB60 4A/600V SHI	74.9°C	85.6°C	4	C10	22U/50V NIPPON 105°C	55.5°C	65.7°C	5	D50	F10SC6 10A/60V SHI	80.9°C	90.2°C	6	Q1	K2628 6A/600V SYNYO	80.5°C	91.9°C	7	D1	EGP20J 2A/600V ZOW	89.0°C	100°C	8	C5	100U/400V RUB 105°C	52.3°C	62.7°C	9	T1 COIL	TF-1017 LS	74.4°C	84.2°C	10	D55	MBR1545CT 15A/45V ON	81.9°C	91.3°C	11	T1 CORE	TF-1017 LS	68.4°C	78.6°C	12	RG1	7905 1A/5V ON	74.2°C	84.1°C	13	C56	2200U/16V RUB 105°C	71.8°C	80.8°C	14	C53	1200U/16V RUB 105°C	65.8°C	74.8°C	15	C51	470U/25V RUB 105°C YXG	67.9°C	77.0°C		
NO	Position	P/N	ROOM AMBIENT Ta= 25.8 °C	HIGH AMBIENT Ta= 36.6 °C																																																																																	
1	LF1	TF-484 LS	59.2°C	68.2°C																																																																																	
2	D56	SR360 3A/60V FMS	79.8°C	89.0°C																																																																																	
3	BD1	D3SB60 4A/600V SHI	74.9°C	85.6°C																																																																																	
4	C10	22U/50V NIPPON 105°C	55.5°C	65.7°C																																																																																	
5	D50	F10SC6 10A/60V SHI	80.9°C	90.2°C																																																																																	
6	Q1	K2628 6A/600V SYNYO	80.5°C	91.9°C																																																																																	
7	D1	EGP20J 2A/600V ZOW	89.0°C	100°C																																																																																	
8	C5	100U/400V RUB 105°C	52.3°C	62.7°C																																																																																	
9	T1 COIL	TF-1017 LS	74.4°C	84.2°C																																																																																	
10	D55	MBR1545CT 15A/45V ON	81.9°C	91.3°C																																																																																	
11	T1 CORE	TF-1017 LS	68.4°C	78.6°C																																																																																	
12	RG1	7905 1A/5V ON	74.2°C	84.1°C																																																																																	
13	C56	2200U/16V RUB 105°C	71.8°C	80.8°C																																																																																	
14	C53	1200U/16V RUB 105°C	65.8°C	74.8°C																																																																																	
15	C51	470U/25V RUB 105°C YXG	67.9°C	77.0°C																																																																																	
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 125% Ta:25°C	TEST : OK	P																																																																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100 % LOAD Ta= -25 °C	TEST : OK	P																																																																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 °C NO DAMAGE	I/P: 230 VAC O/P: FULL LOAD Ta= 40 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																
5	TEMPERATURE COEFFICIENT	± 0.03 % (0-50°C)	I/P: 230 VAC O/P: FULL LOAD	± 0.01 % (0-50°C)	P																																																																																
6	VIBRATION TEST	1 Set Operating at I/P: 230 VAC NO LOAD (1) Waveform: Sine Wave (2) Frequency: 10-500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 1 hour in each axis (X.Y.Z) (6) Ta: 25°C		TEST : OK	P																																																																																

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.0 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 3.49 mA I/P-FG: 2.65 mA O/P-FG: 2.3 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 18G Ω I/P-FG: 15G Ω O/P-FG: 10G Ω NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C	8 mΩ	P
4	APPROVAL	TUV: Certificate NO : R50046939 UL: File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C 56 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 75208 HRS I/P: 230VAC O/P:FULL LOAD Ta= 40 °C LIFE TIME= 30126 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 169.2K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated K2628 : 600 V 6 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 420 V (2) 542 V (3) 550 V	P
2	Diode Peak Voltage	D55 Rated MBR1545CT : 45 V 15 A D50 Rated BYQ28X-200 : 200V 10A D56 Rated UF3004 : 400V 3A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 31.8 V (2) 33.4 V (3) 30 V (1) 62.4 V (2) 69.6 V (3) 69.6 V (1) 104 V (2) 111 V (3) 114 V	P
3	Clamp Diode Peak Voltage	D1 Rated EGP20J : 600 V 2A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 532 V (2) 532 V	P
4	Input Capacitor Voltage	C 5 Rated : 150 u / 400 V/ 105°C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 380 V (2) 386V (3) 374V	P
5	Control IC Voltage Test	U 1 Rated 1203 : 16 V	I/P:High-Line +3V =267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 12.8 V (4) 12.8 V (5) 10.6V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2004/3/2	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2004/10/14	PRODUCT SAMPLE W0409B16	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023