



Test Report: RSP-320-48

320W Single Output With PFC Function

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 240 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 25.2 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 41V ~56V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	39.67 V ~ 57.47 V / 230 VAC 39.67 V ~ 57.47 V / 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %~ -1% (Max)	I/P : 100VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.03 %~ -0.03 %	P
4	LINE REGULATION	V1 : 0.2%~ -0.2% (Max)	I/P : 100VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.02 %~ -0.02 %	P
5	LOAD REGULATION	V1 : 0.5%~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.02 %~ -0.02 %	P
6	SET UP TIME	230VAC : 1500 ms (Max) 115VAC : 3000 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 487 ms 115VAC/ 1320 ms	P
7	RISE TIME	230VAC : 50 ms (Max) 115VAC : 50 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 18 ms 115VAC/ 18 ms	P
8	HOLD UP TIME	230VAC : 8 ms (TYP) 115VAC : 8 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 22 ms 115VAC/ 17 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 4800 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)810 mVp-p (2)750 mVp-p (3)570 mVp-p (4)510 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	61V~264V	P
			I/P : LOW-LINE -3V= 97 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL -MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.981 / 230 VAC PF= 0.996 / 115 VAC	P
4	EFFICIENCY	90 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.1 %	P
5	INPUT CURRENT	230V/ 2 A (TYP) 115V/ 4 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 1.51 A/ 230 VAC I = 3.75 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 40 A (TYP) 115V/ 20 A (TYP) COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 30 A/ 230 VAC I = 15 A/ 115 VAC	P
7	LEAKAGE CURRENT	< 1 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.66 mA N-FG : 0.66 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 % ~ 135 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	118%/ 230 VAC 118%/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1 : 58.4V ~ 68V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	63.8V/ 230 VAC 63.8V/ 115 VAC HOLD ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 85±5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated : STP14NM50N 12A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 429 V (2) 441 V (3) 401 V	P
2	Diode Peak Voltage	Q102 Rated : FMX-12SL 10A/200V Q104 Rated : SF20LC30 20A/300V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 152 V (2) 150 V (3) 154 V (1) 220 V (2) 178 V (3) 228 V	P
3	Input Capacitor Voltage	C 5 Rated : 180u/400V 105°C 18*40 KMG (SURGE VOLTAGE 450V)	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 393 V (2) 405 V (3) 417 V	P
4	Control IC Voltage Test	U 1 Rated : PWM FAN4800AUN 12V~30V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 18.8 V (2) 19.9 V (3) 17.4 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q 2 Rated : STP19NM50N 13A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 401 V (2) 368 V (3) 417 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 2 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 5.85 mA I/P-FG : 5.43 mA O/P-FG : 8.92 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C / 70%RH	I/P-O/P : 7.34 GΩ I/P-FG : 5.94 GΩ O/P-FG : 6.87 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	2 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV L,N-PE : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																									
1	TEMPERATURE RISE TEST	MODEL : RSP-320-24 1. ROOM AMBIENT BURN-IN : 15 HRS I/P : 230VAC O/P : FULL LOAD Ta= 31.9 °C 2. HIGH AMBIENT BURN-IN : 7 HRS I/P : 230VAC O/P : FULL LOAD Ta=49.5 °C			P																																																																																																									
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>PART NUMBER</th> <th>ROOM AMBIENT Ta=31.9 °C</th> <th>HIGH AMBIENT Ta=49.5 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR1021</td><td>43.3°C</td><td>63.5°C</td></tr> <tr><td>2</td><td>C10</td><td>105/450V 10% P=15 B32672P4</td><td>40.9°C</td><td>61.0°C</td></tr> <tr><td>3</td><td>BD1</td><td>10A/800V GLASS KBJ1008G</td><td>46.1°C</td><td>65.9°C</td></tr> <tr><td>4</td><td>D1</td><td>STTH8S06D 8A/600V TO220</td><td>48.2°C</td><td>67.7°C</td></tr> <tr><td>5</td><td>Q2</td><td>STP19NM50N 13A/500V TO220</td><td>42.1°C</td><td>62.7°C</td></tr> <tr><td>6</td><td>Q3</td><td>STP14NM50N 12A/500V TO220</td><td>43.1°C</td><td>64.4°C</td></tr> <tr><td>7</td><td>C5</td><td>180u/400V 105°C 18*40 KMG</td><td>35.1°C</td><td>55.7°C</td></tr> <tr><td>8</td><td>L1</td><td>TR1022</td><td>44.6°C</td><td>65.3°C</td></tr> <tr><td>9</td><td>U1</td><td>FAN4800AUN</td><td>36.3°C</td><td>56.4°C</td></tr> <tr><td>10</td><td>T2</td><td>TR1048</td><td>34.0°C</td><td>55.1°C</td></tr> <tr><td>11</td><td>C18</td><td>47u/50V L5Kh 6.3*11 YXF</td><td>37.1°C</td><td>57.3°C</td></tr> <tr><td>12</td><td>T1 COIL</td><td>TF2438</td><td>51.9°C</td><td>71.6°C</td></tr> <tr><td>13</td><td>TSW1</td><td>ST-22W-R0 85°C 100mm</td><td>44.1°C</td><td>64.2°C</td></tr> <tr><td>14</td><td>RTH2</td><td>5KΩ 5Φ TDC05C20J 5%</td><td>41.0°C</td><td>60.8°C</td></tr> <tr><td>15</td><td>Q201</td><td>TIP122 5A/100V TO220</td><td>48.2°C</td><td>66.7°C</td></tr> <tr><td>16</td><td>Q101</td><td>STPS20120CT 20A/120V TO220</td><td>54.0°C</td><td>73.9°C</td></tr> <tr><td>17</td><td>Q104</td><td>STPS20120CT 20A/120V TO220</td><td>44.8°C</td><td>64.3°C</td></tr> <tr><td>18</td><td>L100</td><td>TR1064</td><td>59.0°C</td><td>80.1°C</td></tr> <tr><td>19</td><td>C105</td><td>1000u/35V UL10Kh 12.5*20 ZLH</td><td>51.2°C</td><td>71.5°C</td></tr> <tr><td>20</td><td>C203</td><td>100u/25V L5Kh 6.3*11 KY</td><td>39.2°C</td><td>59.3°C</td></tr> </tbody> </table>				NO	Position	PART NUMBER	ROOM AMBIENT Ta=31.9 °C	HIGH AMBIENT Ta=49.5 °C	1	LF1	TR1021	43.3°C	63.5°C	2	C10	105/450V 10% P=15 B32672P4	40.9°C	61.0°C	3	BD1	10A/800V GLASS KBJ1008G	46.1°C	65.9°C	4	D1	STTH8S06D 8A/600V TO220	48.2°C	67.7°C	5	Q2	STP19NM50N 13A/500V TO220	42.1°C	62.7°C	6	Q3	STP14NM50N 12A/500V TO220	43.1°C	64.4°C	7	C5	180u/400V 105°C 18*40 KMG	35.1°C	55.7°C	8	L1	TR1022	44.6°C	65.3°C	9	U1	FAN4800AUN	36.3°C	56.4°C	10	T2	TR1048	34.0°C	55.1°C	11	C18	47u/50V L5Kh 6.3*11 YXF	37.1°C	57.3°C	12	T1 COIL	TF2438	51.9°C	71.6°C	13	TSW1	ST-22W-R0 85°C 100mm	44.1°C	64.2°C	14	RTH2	5KΩ 5Φ TDC05C20J 5%	41.0°C	60.8°C	15	Q201	TIP122 5A/100V TO220	48.2°C	66.7°C	16	Q101	STPS20120CT 20A/120V TO220	54.0°C	73.9°C	17	Q104	STPS20120CT 20A/120V TO220	44.8°C	64.3°C	18	L100	TR1064	59.0°C	80.1°C	19	C105	1000u/35V UL10Kh 12.5*20 ZLH	51.2°C	71.5°C	20	C203	100u/25V L5Kh 6.3*11 KY	39.2°C	59.3°C
		NO				Position	PART NUMBER	ROOM AMBIENT Ta=31.9 °C	HIGH AMBIENT Ta=49.5 °C																																																																																																					
		1				LF1	TR1021	43.3°C	63.5°C																																																																																																					
		2				C10	105/450V 10% P=15 B32672P4	40.9°C	61.0°C																																																																																																					
		3				BD1	10A/800V GLASS KBJ1008G	46.1°C	65.9°C																																																																																																					
		4				D1	STTH8S06D 8A/600V TO220	48.2°C	67.7°C																																																																																																					
		5				Q2	STP19NM50N 13A/500V TO220	42.1°C	62.7°C																																																																																																					
		6				Q3	STP14NM50N 12A/500V TO220	43.1°C	64.4°C																																																																																																					
		7				C5	180u/400V 105°C 18*40 KMG	35.1°C	55.7°C																																																																																																					
		8				L1	TR1022	44.6°C	65.3°C																																																																																																					
		9				U1	FAN4800AUN	36.3°C	56.4°C																																																																																																					
		10				T2	TR1048	34.0°C	55.1°C																																																																																																					
		11				C18	47u/50V L5Kh 6.3*11 YXF	37.1°C	57.3°C																																																																																																					
		12				T1 COIL	TF2438	51.9°C	71.6°C																																																																																																					
		13				TSW1	ST-22W-R0 85°C 100mm	44.1°C	64.2°C																																																																																																					
		14				RTH2	5KΩ 5Φ TDC05C20J 5%	41.0°C	60.8°C																																																																																																					
		15				Q201	TIP122 5A/100V TO220	48.2°C	66.7°C																																																																																																					
		16				Q101	STPS20120CT 20A/120V TO220	54.0°C	73.9°C																																																																																																					
		17				Q104	STPS20120CT 20A/120V TO220	44.8°C	64.3°C																																																																																																					
		18				L100	TR1064	59.0°C	80.1°C																																																																																																					
19	C105	1000u/35V UL10Kh 12.5*20 ZLH	51.2°C	71.5°C																																																																																																										
20	C203	100u/25V L5Kh 6.3*11 KY	39.2°C	59.3°C																																																																																																										
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 118 % LOAD Ta : 25°C	TEST : OK	P																																																																																																									
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -35 °C	TEST : OK	P																																																																																																									
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																									
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0-50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.003 %/°C (0-50°C)	P																																																																																																									

6	STORAGE TEMPERATURE TEST	<ol style="list-style-type: none"> 1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC 	OK	P	
7	THERMAL SHOCK TEST	<ol style="list-style-type: none"> 1. Thermal shock Temperature : -35°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec 	OK	P	
8	VIBRATION TEST	1 Carton & 1 Set <ol style="list-style-type: none"> (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C 	TEST : OK	P	
9	CAPACITOR LIFE CYCLE	RSP-320-24:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT <ol style="list-style-type: none"> (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta=50 °C LIFE TIME 	<ol style="list-style-type: none"> (1) 814893HRS (2) 119480HRS (3) 195414HRS (4) 238961HRS 	P	
10	MTBF	MIL-HDBK-217F NOTICE S2 PARTS COUNT TOTAL FAILURE RATE : 206.5 KHRS			
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50°C			P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2012/8/7	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/8/27	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023