

Quality Engineering Test Report

SERIES: SD-50A 25W DC-DC SINGLE OUTPUT SWITCHING POWER SUPPLY

SAMPLE: A. SD-50A-5 5V / 10A
B. SD-50A-12 12V / 4.2A
C. SD-50A-24 24V / 2.1A

NO	TEST ITEM	TEST CONDITION / SPECIFICATION	RESULT	VERDICT
1	DC INPUT VOLTAGE RANGE	I/P: TESTING SPEC: 9.2~18VDC O/P:FULL LOAD	A:9.2~18VDC	P
2	LINE REGULATION	I/P: 9.2~18VDC SPEC: A:±0.5% O/P: FULL LOAD B:±0.3% C:±0.2%	A:-0.12%~+0% B: -0%~+0% C: -0%~+0%	P
3	LOAD REGULATION	I/P: 12VDC SPEC: A:±0.5% O/P: MIN. TO FULL LOAD B:±0.3% C:±0.2%	A:-0.24%~+0% B: -0%~+0% C: -0.03%~+0%	P
4	OUTPUT VOLTAGE TOLERANCE	I/P: 9.2~18VDC SPEC: A:±2% O/P: MIN. TO FULL LOAD B:±1% C:±1%	A:-0.24%~+0% B: -0 %~+0% C:-0.03%~+0%	P
5	RIPPLE&NOISE	I/P: 12VDC SPEC: A:100mVp-p O/P: FULL LOAD B:120mVp-p C:150mVp-p	A:8mV B:4mV C:9mV	P
6	DC INPUT CURRENT	I/P: 12VDC SPEC: 7A O/P:FULL LOAD	A:5.88A	P
7	MAX. INRUSH CURRENT	I/P: 12VDC SPEC: NONE O/P:FULL LOAD	A:23.3A	P
8	O/P VOLTAGE ADJ. RANGE	I/P: 12VDC SPEC: A:4.5~5.5V O/P: MIN. LOAD B:11~16V C:23~30V	A:4.43~6.21V B:9.69~16.36V C:19.76~33.41V	P
9	SET UP TIME	I/P: 12VDC SPEC: 2.5S O/P:FULL LOAD	A:430.4mS	P
10	EFFICIENCY	I/P: 12VDC SPEC: A:70% O/P: FULL LOAD B:72% C:74%	A:70% B:74% C:77%	P
11	OVER LOAD PROTECTION	I/P: 12VDC SPEC: 105%~150% O/P: TESTING	A:120% B:126% C:105.2%	P
12	OVER VOLTAGE PROTECTION	I/P: 12VDC SPEC: A:5.75V~6.75V O/P: TESTING B:16.8V~20V C:31.5V~37.5V	A:6.16V B:18.52V C:35.64V	P
13	INSULATION RESISTANCE	SPEC: I/P-O/P 500VDC/100M Ohms MIN. I/P-FG 500VDC/100M Ohms MIN. O/P-FG 500VDC/100M Ohms MIN.	A: I/P-O/P:>100M Ohms I/P-FG :>100M Ohms O/P-FG :>100M Ohms	P
14	DIELECTRIC / WITHSTAND VOLTAGE	SPEC: I/P- O/P: 1500VAC/ 1 min (10mA CUT-OFF) I/P- FG: 1500VAC/ 1 min (10mA CUT-OFF) O/P- FG: 500VAC/ 1 min (10mA CUT-OFF)	A: I/P-O/P:<1.9mA I/P-FG:<2.1mA O/P-FG:<3.92mA	P
15	BURN-IN TEST	I/P : 12VDC O/P:FULL LOAD TA : 25 °C BURN-IN DURATION : 4 hrs	NON BREAK	P
16	ENVIRONMENT TEST (SAMPLE A:)	HIGH AMBIENT TEMPERATURE FULL LOAD TEST I/P:12VDC O/P:FULL LOAD AMBIENT TEMPERATURE:37.40°C	AFTER 3 hrs NON BREAK	P

NO	TEST ITEM	TEST CONDITION / SPECIFICATION	RESULT	VERDICT																												
17	TEMPERATURE RISE TEST T rise OF PARTS	<p>A: I/P : 12VDC AFTER 4 hrs BURN-IN O/P : FULL LOAD TA : 24.9°C</p> <table border="1"> <thead> <tr> <th>POSITION</th> <th>P/N</th> <th>TEMP</th> <th>T rise</th> </tr> </thead> <tbody> <tr> <td>Q1</td> <td>MAIN TRANSISTOR</td> <td>87.0°C</td> <td>62.1°C</td> </tr> <tr> <td>T1</td> <td>MAIN TRANSFORMER</td> <td>82.6°C</td> <td>57.7°C</td> </tr> <tr> <td>D11</td> <td>O/P DIODE</td> <td>74.3°C</td> <td>49.4°C</td> </tr> <tr> <td>C34</td> <td>O/P FILTER CAPACITOR</td> <td>61.7°C</td> <td>36.8°C</td> </tr> <tr> <td>L1</td> <td>O/P CHOCK</td> <td>70.1°C</td> <td>45.2°C</td> </tr> <tr> <td>C5</td> <td>I/P FILTER CAPACITOR</td> <td>59.8°C</td> <td>34.9°C</td> </tr> </tbody> </table>	POSITION	P/N	TEMP	T rise	Q1	MAIN TRANSISTOR	87.0°C	62.1°C	T1	MAIN TRANSFORMER	82.6°C	57.7°C	D11	O/P DIODE	74.3°C	49.4°C	C34	O/P FILTER CAPACITOR	61.7°C	36.8°C	L1	O/P CHOCK	70.1°C	45.2°C	C5	I/P FILTER CAPACITOR	59.8°C	34.9°C		P
POSITION	P/N	TEMP	T rise																													
Q1	MAIN TRANSISTOR	87.0°C	62.1°C																													
T1	MAIN TRANSFORMER	82.6°C	57.7°C																													
D11	O/P DIODE	74.3°C	49.4°C																													
C34	O/P FILTER CAPACITOR	61.7°C	36.8°C																													
L1	O/P CHOCK	70.1°C	45.2°C																													
C5	I/P FILTER CAPACITOR	59.8°C	34.9°C																													
18	LIFE CYCLE	<p>A: SUPPOSE C34 IS THE MOST CRITICAL COMPONENT I/P : 12VDC O/P : FULL LOAD Ta : 25°C Tc34 : 61.8°C Life: 39946 hrs I/P : 12VDC O/P : FULL LOAD Ta : 37.42°C Tc34 : 78.5°C Life: 12553 hrs</p>		P																												
19	CRITICAL COMPONENT RECORD (FOR QC INSPECTION REFERENCE ONLY)	<p>A: FUSE : F 15A/250V G PH UL INPUT DIODE : 1N5401 LINE FILTER : TF-096A EE-25 TRANSFOMER : MT TF-321-R1 EI-28 POWER SWITCHER : 2SK2049 TO-220 OUTPUT DIODE : CTB-34M TO-3P OUTPUT CAPACITOR : 2200uF/16V(v) 105°C HL INPUT CAPACITOR : 220uF/100V(v) 105°C HL P.C.B : SD-50 FR-4 2 OZ DS</p>																														
DATE	SAMPLE	TEST RESULT	TEST	APPROVAL																												
980422	SD-50A	PASS	H.C.LIOU	Max Lin																												