



MODEL : SDR-480-48

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 120 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 29.6 mVp-p (Max)	P
2	PEAK POWER	V1 : 720W (>3sec.)	I/P : 230VAC O/P : 720W Ta : 25°C	OK	P
3	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 48 V- 55V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	46.35 V- 56.29 V/ 230 VAC 46.35 V- 56.28 V/ 115 VAC	P
4	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %- -1 % (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.3 %- -0.3 %	P
5	LINE REGULATION	V1 : 0.5 %- -0.5 % (Max)	I/P : 100VAC - 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.02 %- -0.02 %	P
6	LOAD REGULATION	V1 : 1 %- -1 % (Max)	I/P : 230 VAC O/P : FULL -MIN LOAD Ta : 25°C	V1 : 0.27 %- -0.27 %	P
7	SET UP TIME	230VAC : 1500 ms (Max) 115 VAC : 3000 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 577 ms 115VAC/ 1154 ms	P
8	RISE TIME	230VAC : 150 ms (Max) 115VAC : 150 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 108 ms 115VAC/ 101 ms	P
9	HOLD UP TIME	230VAC : 14 ms (TYP) 115VAC : 14 ms (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 17.9 ms 115 VAC 18 ms	P
10	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 5 %	P
11	DYNAMIC LOAD	V1 : 4800 mVp-p	I/P : 230 VAC O/P : FULL /Min LOAD 90%DUTY/1KHZ Ta : 25°C	514 mVp-p	P



**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC-264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	80 V -264V	P
			I/P : LOW-LINE-3V= 87V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ -63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.92 / 230 VAC(TYP) 0.99 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.952 / 230 VAC PF= 1 / 115 VAC	P
4	EFFICIENCY	94% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	94.4 %	P
5	INPUT CURRENT	230V/ 2.5 A (TYP) 115V/ 5 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 2.30 A/ 230 VAC I = 4.50 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 80 A (TYP) 115V/ 40 A(TYP) COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 58 A/ 230 VAC I = 30 A/ 115 VAC	P
7	LEAKAGE CURRENT	< 0.8 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.5 mA N-FG : 0.5 mA	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 %~ 150 %  Normally works within 110 ~ 150% rated output power for more than 3 seconds and then shut down o/p voltage with auto-recovery >150% rated power, constant current limiting with auto-recovery within 2 seconds and may cause to shut down if over 2 seconds	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	118 %/ 230 VAC 117 %/ 115 VAC  Normally works within 110 ~ 150% rated output power for more than 3 seconds and then shut down o/p voltage with auto-recovery >150% rated power, constant current limiting with auto-recovery within 2 seconds and may cause to shut down if over 2 seconds	P
2	OVER VOLTAGE PROTECTION	CH1 : 56 V- 65V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	59.5 V/ 230 VAC 59.5 V/ 115 VAC Shut down o/p voltage with auto-recovery or re-power on to recovery	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 105 ± 5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage · recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Shut down Re-power ON	P

**CONTROL FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	DC OK REALY CONTACT RATINGS (max.)	60Vdc/0.3A, 30Vdc/1A, 30Vac/0.5A resistive load	I/P : 230 VAC O/P : FULL LOAD	OK	P



ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																																																	
1	TEMPERATURE RISE TEST	MODEL : SDR-480-24 1. ROOM AMBIENT BURN-IN : 2.5HRS I/P : 230VAC O/P : FULL LOAD Ta= 30.2 °C 2. HIGH AMBIENT BURN-IN : 1.5HRS I/P : 230VAC O/P : FULL LOAD Ta= 59.6 °C			P																																																																																																																																	
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta=30.2 °C</th> <th>HIGH AMBIENT Ta= 59.6 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR835 155°C</td><td>56.9°C</td><td>86.6°C</td></tr> <tr><td>2</td><td>LF2</td><td>TR831 155°C</td><td>60.7°C</td><td>89.5°C</td></tr> <tr><td>3</td><td>L6</td><td>TR836 155°C</td><td>60.3°C</td><td>89.1°C</td></tr> <tr><td>4</td><td>BD1</td><td>30A/800V US30KB80R</td><td>65.1°C</td><td>93.3°C</td></tr> <tr><td>5</td><td>Q901</td><td>STW25NM50N 22A/500V</td><td>57.8°C</td><td>88.0°C</td></tr> <tr><td>6</td><td>D902</td><td>BYT79X-600 15A/600V</td><td>58.2°C</td><td>88.4°C</td></tr> <tr><td>7</td><td>C901</td><td>180U/450V HU</td><td>58.4°C</td><td>88.0°C</td></tr> <tr><td>8</td><td>C902</td><td>150u/420V 105°C KMG</td><td>68.3°C</td><td>97.9°C</td></tr> <tr><td>9</td><td>C42</td><td>220u/35V UL7Kh KY</td><td>71.3°C</td><td>100.9°C</td></tr> <tr><td>10</td><td>U2</td><td>L6599D</td><td>66.7°C</td><td>96.0°C</td></tr> <tr><td>11</td><td>C47</td><td>47u/25V UL10Kh YXM</td><td>68.3°C</td><td>97.4°C</td></tr> <tr><td>12</td><td>C46</td><td>47u/25V UL10Kh 5*11 YXM</td><td>66.2°C</td><td>95.4°C</td></tr> <tr><td>13</td><td>Q40</td><td>IRFB20N50K 20A/500V</td><td>59.4°C</td><td>89.7°C</td></tr> <tr><td>14</td><td>Q100</td><td>IRFB3307 130A/75V TO220</td><td>66.6°C</td><td>99.0°C</td></tr> <tr><td>15</td><td>C103</td><td>1500u/35V UL10Kh ZLH</td><td>55.3°C</td><td>85.5°C</td></tr> <tr><td>16</td><td>C106</td><td>1500u/35V UL10Kh ZLH</td><td>71.5°C</td><td>102.1°C</td></tr> <tr><td>17</td><td>C108</td><td>680u/35V UL10Kh ZLH</td><td>70.0°C</td><td>99.9°C</td></tr> <tr><td>18</td><td>C183</td><td>470u/35V UL7Kh 10*20 KY</td><td>64.8°C</td><td>91.9°C</td></tr> <tr><td>19</td><td>L180</td><td>TR830</td><td>72.2°C</td><td>100.6°C</td></tr> <tr><td>20</td><td>C121</td><td>390u/35V UL8Kh ZLH</td><td>71.4°C</td><td>101.4°C</td></tr> <tr><td>21</td><td>C122</td><td>220u/35V UL7Kh KY</td><td>70.3°C</td><td>99.3°C</td></tr> <tr><td>22</td><td>T902</td><td>TF1886</td><td>71.2°C</td><td>99.6°C</td></tr> <tr><td>23</td><td>TSW1</td><td>105°C</td><td>57.5°C</td><td>87.3°C</td></tr> <tr><td>24</td><td>Q907</td><td>STD1NK60-1 1A/600V IPAK</td><td>47.6°C</td><td>76.0°C</td></tr> <tr><td>25</td><td>T1</td><td>TF1885 155°C</td><td>96.1°C</td><td>125.6°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta=30.2 °C	HIGH AMBIENT Ta= 59.6 °C	1	LF1	TR835 155°C	56.9°C	86.6°C	2	LF2	TR831 155°C	60.7°C	89.5°C	3	L6	TR836 155°C	60.3°C	89.1°C	4	BD1	30A/800V US30KB80R	65.1°C	93.3°C	5	Q901	STW25NM50N 22A/500V	57.8°C	88.0°C	6	D902	BYT79X-600 15A/600V	58.2°C	88.4°C	7	C901	180U/450V HU	58.4°C	88.0°C	8	C902	150u/420V 105°C KMG	68.3°C	97.9°C	9	C42	220u/35V UL7Kh KY	71.3°C	100.9°C	10	U2	L6599D	66.7°C	96.0°C	11	C47	47u/25V UL10Kh YXM	68.3°C	97.4°C	12	C46	47u/25V UL10Kh 5*11 YXM	66.2°C	95.4°C	13	Q40	IRFB20N50K 20A/500V	59.4°C	89.7°C	14	Q100	IRFB3307 130A/75V TO220	66.6°C	99.0°C	15	C103	1500u/35V UL10Kh ZLH	55.3°C	85.5°C	16	C106	1500u/35V UL10Kh ZLH	71.5°C	102.1°C	17	C108	680u/35V UL10Kh ZLH	70.0°C	99.9°C	18	C183	470u/35V UL7Kh 10*20 KY	64.8°C	91.9°C	19	L180	TR830	72.2°C	100.6°C	20	C121	390u/35V UL8Kh ZLH	71.4°C	101.4°C	21	C122	220u/35V UL7Kh KY	70.3°C	99.3°C	22	T902	TF1886	71.2°C	99.6°C	23	TSW1	105°C	57.5°C	87.3°C	24	Q907	STD1NK60-1 1A/600V IPAK	47.6°C	76.0°C	25	T1	TF1885 155°C	96.1°C	125.6°C	
NO	Position	P/N	ROOM AMBIENT Ta=30.2 °C	HIGH AMBIENT Ta= 59.6 °C																																																																																																																																		
1	LF1	TR835 155°C	56.9°C	86.6°C																																																																																																																																		
2	LF2	TR831 155°C	60.7°C	89.5°C																																																																																																																																		
3	L6	TR836 155°C	60.3°C	89.1°C																																																																																																																																		
4	BD1	30A/800V US30KB80R	65.1°C	93.3°C																																																																																																																																		
5	Q901	STW25NM50N 22A/500V	57.8°C	88.0°C																																																																																																																																		
6	D902	BYT79X-600 15A/600V	58.2°C	88.4°C																																																																																																																																		
7	C901	180U/450V HU	58.4°C	88.0°C																																																																																																																																		
8	C902	150u/420V 105°C KMG	68.3°C	97.9°C																																																																																																																																		
9	C42	220u/35V UL7Kh KY	71.3°C	100.9°C																																																																																																																																		
10	U2	L6599D	66.7°C	96.0°C																																																																																																																																		
11	C47	47u/25V UL10Kh YXM	68.3°C	97.4°C																																																																																																																																		
12	C46	47u/25V UL10Kh 5*11 YXM	66.2°C	95.4°C																																																																																																																																		
13	Q40	IRFB20N50K 20A/500V	59.4°C	89.7°C																																																																																																																																		
14	Q100	IRFB3307 130A/75V TO220	66.6°C	99.0°C																																																																																																																																		
15	C103	1500u/35V UL10Kh ZLH	55.3°C	85.5°C																																																																																																																																		
16	C106	1500u/35V UL10Kh ZLH	71.5°C	102.1°C																																																																																																																																		
17	C108	680u/35V UL10Kh ZLH	70.0°C	99.9°C																																																																																																																																		
18	C183	470u/35V UL7Kh 10*20 KY	64.8°C	91.9°C																																																																																																																																		
19	L180	TR830	72.2°C	100.6°C																																																																																																																																		
20	C121	390u/35V UL8Kh ZLH	71.4°C	101.4°C																																																																																																																																		
21	C122	220u/35V UL7Kh KY	70.3°C	99.3°C																																																																																																																																		
22	T902	TF1886	71.2°C	99.6°C																																																																																																																																		
23	TSW1	105°C	57.5°C	87.3°C																																																																																																																																		
24	Q907	STD1NK60-1 1A/600V IPAK	47.6°C	76.0°C																																																																																																																																		
25	T1	TF1885 155°C	96.1°C	125.6°C																																																																																																																																		
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P : 230 VAC O/P : 120 % LOAD Ta : 25°C	TEST : OK	P																																																																																																																																	
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 230 VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK	P																																																																																																																																	
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																																	
5	TEMPERATURE COEFFICIENT	± 0.03 % (0-50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.056 % (0-50°C)	P																																																																																																																																	
6	VIBRATION TEST	A.1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 2G (5) Test Time : 1 hour in each axis (X.Y.Z) (6) Ta : 25°C B. 1 Set Mounting : Compliance to IEC60068-2-6		TEST : OK	P																																																																																																																																	



**SAFETY TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 1.5 KVAC/min O/P-FG : 0.5 KVAC/min O/P-DC OK : 0.5KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 1.8 KVAC/min O/P-FG : 0.6 KVAC/min O/P-DC OK : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 5.53 mA I/P-FG : 4.13 mA O/P-FG : 23.71 mA O/P-DC OK : 0.029 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 24.3 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	16 mΩ	P
4	APPROVAL	TUV : Certificate NO : R50148750 UL : File NO : E215312			P

**E.M.C TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230/240/220 VAC/50HZ O/P : 100/75/50/25%LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 EN55011 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 EN55011 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

**M.T.B.F & LIFE CYCLE CALCULATION**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SDR-480-24 : SUPPOSE C 106 IS THE MOST CRITICAL COMPONENT	I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME= 179679 HRS I/P : 230VAC O/P : FULL LOAD Ta= 60 °C LIFE TIME= 14625 HRS I/P : 230VAC O/P : 75%OAD Ta= 60 °C LIFE TIME= 38099 HRS		P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 112.9K HRS			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 60°C			P



**COMPONENT STRESS TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S) or (C to E) Peak Voltage	Q 40 Rated IRFB20N50K 20A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short Ta : 25°C	(1) 446 V (2) 404 V	P
2	Diode Peak Voltage	Q100 Rated YA868C15RSC 30A/150V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short Ta : 25°C	(1) 40 V (2) 108 V	P
3	PFC Transistor ( D to S) or (C to E) Peak Voltage	Q902 Rated STW25NM50N 22A/550V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short Ta : 25°C	(1) 548 V (2) 422 V	P
4	Clamp Diode Peak Voltage	D41 / 42 Rated SBD MBR1200 1A/200V	I/P : High-Line +3V = 267 V O/P : (1) Dynamic Load 90%Duty/1KHz Ta : 25°C	(1) 20.1 / 20 V	P
5	Input Capacitor Voltage	C901 Rated 180u/450V 105°C 25*30 HU	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 391.2 V (2) 392.6 V (3) 392.3 V	P
6	Control IC Voltage Test	U2 Rated L6599D 16V (max) 8.85V (min)	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 12.352 V (2) 12.288 V (3) 12.288 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2008/11/10	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2009/5/5	PRODUCT SAMPLE W0902A49	PASS	SANFORD SU	VINCENT TSENG
2009/6/16	PRODUCT SAMPLE W0905A47	PASS	SANFORD SU	VINCENT TSENG

2003/12/12 A50-F023