



# Test Report: HLG-480H-48

---

480W Constant Voltage + Constant Current LED Driver

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test



## ■ RELIABILITY TEST

ENVIRONMENT TEST


■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONSTANT CURRENT REGION	CH1: 24 V- 48V	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	0.061V-48 V /230VAC
2	VOLTAGE ADJUST RANGE	CH1: 40.8 V- 50.4V	I/P: 230 VAC I/P:115VAC O/P:MIN LOAD Ta:25°C	37.269V-51.698V /230VAC 37.251V-51.693 V/115VAC
3	CURRENT ADJ. RANGE	CH1: 5 A- 10 A	I/P: 230 VAC I/P:115VAC O/P:CV MIN & CV MAX-1V Ta:25°C	3.796A-10.757A /230VAC@CV MAX-1V 3.795A-10.781 A /230VAC@CV MIN 3.797A-10.76A/115VAC@CV MAX-1V 3.804A- 10.783A/115VAC@CV MIN
4	OUTPUT VOLTAGE TOLERANCE (Max)	V1:1% ~ -1 %	I/P:100VAC /305AC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.187 %---0.375%
5	LINE REGULATION (Max)	V1: 0.5% ~ -0.5 %	I/P:100VAC-305AC O/P:FULL LOAD Ta:25°C	V1: 0.04%---0.02%
6	LOAD REGULATION (Max)	V1: 0.5 % ~ -0.5 %	I/P: 230 VAC O/P:FULL -MIN LOAD Ta:25°C	V1: 0.166%--0.333%
7	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5%
8	RIPPLE & NOISE (Max )	V1: 250 mVp-p	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 186mVp-p




9	SET UP TIME (Max)	230VAC/ 500 ms 115VAC/ 500 ms	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/199ms 115 VAC/232ms
INPUT=230VAC/50HZ @ FULL LOAD		INPUT=115VAC/60HZ @ FULL LOAD CH1 : Output Voltage CH2 : AC Input Voltage		



10	RISE TIME (Max)	230VAC/ 80 ms	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	230VAC/	38.4ms
		115VAC/ 80 ms		115 VAC/	38.8ms


INPUT=230VAC/50HZ @ FULL LOAD

CH1 : Output Voltage



INPUT=115VAC/60HZ @ FULL LOAD


CH1 : Output Voltage



11	HOLD UP TIME (Typ.)	230VAC/ 16 ms	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	230VAC/	29.2ms
		115VAC/ 16 ms		115 VAC/	29.2ms


INPUT=230VAC/50HZ @ FULL LOAD


CH1 : Output Voltage CH2 : AC Input Voltage



INPUT=115VAC/60HZ @ FULL LOAD


CH1 : Output Voltage CH2 : AC Input Voltage






### INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC-305 VAC	I/P: TESTING O/P: FULL LOAD Ta:25°C	76V-305 V
			I/P: LOW-LINE-3V=87 V HIGH-LINE+10V=315 V O/P: FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec OFF: 30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	TEST:OK
2	INPUT FREQUENCY RANGE	47HZ -63 HZ NO DAMAGE	I/P: 100 VAC ~305VAC O/P: FULL-MIN LOAD Ta:25°C	OK
3	INPUT CURRENT (TYP)	277VAC/ 2 A 230 VAC/ 2.45 A 115 VAC/ 5 A	I/P: 277VAC/230 VAC/115 VAC O/P: FULL LOAD Ta:25°C	I= 1.79A/277VAC I = 2.12A/ 230VAC I = 4.28A/ 115VAC
4	LEAKAGE CURRENT	< 0.75 mA / 277VAC	I/P : 277 VAC O/P : Min LOAD Ta : 25°C	L-FG: 0.32mA N-FG: 0.3mA
6	POWER FACTOR(TYP)	0.97/230 VAC FULL LOAD 0.98/115 VAC FULL LOAD 0.95/277 VAC FULL LOAD	I/P: 230 VAC/115VAC/277VAC O/P: FULL LOAD Ta:25°C	PF= 0.978 /230V/100%LOAD PF= 0.993/115V/100%LOAD PF= 0.958/277V/100%LOAD




7	EFFICIENCY (TYP)	94.5 % 95%	I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta:25°C	94.77% /230V 95.02% /277V
---	------------------	---------------	---	------------------------------



8	INRUSH CURRENT (TYP)	230 V/35A COLD START  (twidth=1800us measured at 50% Ipeak) COLD START	I/P: 230 VAC O/P: FULL LOAD Ta:25°C	I = 33.1A/ 230VAC  T50= 1500 us
---	----------------------	---	---	---------------------------------------

INPUT=230VAC/50HZ @ FULL LOAD

CH2 : AC Input Voltage CH4 : Input current (1V=1A)



9	TOTAL HARMONIC DISTORTION	THD < 20% @ output load ≥ 40% at 115VAC/230/277VAC input	I/P : 115VAC O/P : 100% LOAD 40% LOAD Ta : 25°C	THD : 5.68 % THD : 6.32 %																																												
			I/P : 230VAC O/P : 100% LOAD 40% LOAD Ta : 25°C	THD : 6.28 % THD : 9.54 %																																												
			I/P : 277VAC O/P : 100% LOAD 40% LOAD Ta : 25°C	THD : 8.96 % THD : 15.67 %																																												
<table border="1"> <caption>THD (%) vs LOAD (%) Data</caption> <thead> <tr> <th>LOAD (%)</th> <th>115VAC THD (%)</th> <th>230VAC THD (%)</th> <th>277VAC THD (%)</th> </tr> </thead> <tbody> <tr><td>10%</td><td>10.5</td><td>24.5</td><td>32.5</td></tr> <tr><td>20%</td><td>7.5</td><td>15.5</td><td>24.5</td></tr> <tr><td>30%</td><td>6.5</td><td>11.5</td><td>18.5</td></tr> <tr><td>40%</td><td>6.5</td><td>9.5</td><td>15.5</td></tr> <tr><td>50%</td><td>6.0</td><td>8.5</td><td>13.5</td></tr> <tr><td>60%</td><td>5.5</td><td>7.5</td><td>12.5</td></tr> <tr><td>70%</td><td>5.5</td><td>7.0</td><td>11.5</td></tr> <tr><td>80%</td><td>6.5</td><td>6.5</td><td>10.5</td></tr> <tr><td>90%</td><td>4.5</td><td>6.5</td><td>9.5</td></tr> <tr><td>100%</td><td>7.5</td><td>6.5</td><td>8.5</td></tr> </tbody> </table>					LOAD (%)	115VAC THD (%)	230VAC THD (%)	277VAC THD (%)	10%	10.5	24.5	32.5	20%	7.5	15.5	24.5	30%	6.5	11.5	18.5	40%	6.5	9.5	15.5	50%	6.0	8.5	13.5	60%	5.5	7.5	12.5	70%	5.5	7.0	11.5	80%	6.5	6.5	10.5	90%	4.5	6.5	9.5	100%	7.5	6.5	8.5
LOAD (%)	115VAC THD (%)	230VAC THD (%)	277VAC THD (%)																																													
10%	10.5	24.5	32.5																																													
20%	7.5	15.5	24.5																																													
30%	6.5	11.5	18.5																																													
40%	6.5	9.5	15.5																																													
50%	6.0	8.5	13.5																																													
60%	5.5	7.5	12.5																																													
70%	5.5	7.0	11.5																																													
80%	6.5	6.5	10.5																																													
90%	4.5	6.5	9.5																																													
100%	7.5	6.5	8.5																																													

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95 %- 108 %  PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed	I/P: 305VAC I/P: 230VAC I/P: 100VAC O/P: TESTING Ta: 25°C	102.8%/ 305VAC 103.27%/ 230VAC 103.1%/100VAC PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	V1: 53 V- 63 V  PROTECTION TYPE : Shut down output voltage, re-power on to recovery	I/P: 305VAC I/P: 230VAC I/P: 90VAC O/P: MIN LOAD Ta: 25°C	54.61V/ 305VAC 54.64V/ 230VAC 54.54V/ 90VAC PROTECTION TYPE : Shut down output voltage, re-power on to recovery
3	OVER TEMPERATURE PROTECTION	PROTECTION TYPE : Shut down output voltage, re-power on to recovery	I/P: 305 VAC I/P: 90 VAC O/P: FULL LOAD	O.T.P Active PROTECTION TYPE : Shut down output voltage, re-power on to recovery
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE  PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed	I/P: 305VAC I/P: 90 VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed

**COMPONENT STRESS TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) <b>Peak Voltage</b>	Q 10 Rated 13 A/ 650 V  Q 13Rated 13 A/ 650V	I/P:High-Line +3V =308V AC ON/OFF VDS: O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0%→400% Load. Ta:25°C	Q10 VDS: (1) 490V (2) 478V (3) 494V (4) 490V (5) 494V (6) 490V (7) 474V  Q13 VDS: (1) 534V (2) 522V (3) 534V (4) 530V (5) 530V (6) 530V (7) 518V
2	P.F.C Transistor (D to S) or (C to E) <b>Peak Voltage</b>	Q1 Rated 13 A/650V	I/P:High-Line +3V =308 V AC ON/OFF O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0%→400% Load. Ta:25°C	Q1 VDS: (1) 482V (2) 462V (3) 470V (4) 466V (5)458V (6) 462V (7) 474V
3	P.F.C DIODE	D8 Rated 12A/ 600V	I/P:High-Line +3V =308 V AC ON/OFF O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (4)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz Ta:25°C	D8: 308V (1) 454V (2) 470V (3) 458V (4) 478V
4	Diode <b>Peak Voltage</b>	Q100 Rated 43A/150V  Q101 Rated 43A/150V	I/P:High-Line +3V =308 V AC ON/OFF O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0%→400% Load. (8).NO LOAD Ta:25°C	Q100: VDS: (1) 107.7V (2) 56.2V (3)108.5V (4)111.7V (5) 112.5V (6)112.5V (7)116.5V (8) 115.7V  Q101: VDS: (1) 110.1V (2) 31.3V (3) 109.3V (4) 115.7V (5) 110.9V (6) 110.9V (7)134V (8) 135.4V
5	<b>Input Capacitor Voltage</b>	C5 Rated: 150 μ / 450V	I/P:High-Line +3V =308V O/P: (1)Full Load input on/off	(1) 448V (2) 448V

			(2) Min load input on /Off (3) Full Load /Min load Change (4) Full load continue Ta:25°C	(3) 448V (4) 440V
6	<b>Control IC Voltage Test</b>	PWM IC U2 Rated 16V- 8.85V(MIN.)  PFC IC U1 Rated 20V-10.5V(MIN.)	I/P:High-Line +3V =308 V AC ON/OFF O/P(1)FULL LOAD (2) Output Short (3)O.L.P (4)O.V.P. Ta:25°C	U2 (1) 13.45V (2) 13.37V (3) 13.21V (4) 13.29V  U1 (1) 14.42V (2)14.5V (3) 14.58V (4) 14.1V

## SAFETY & EMC TEST REPORT

### SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	IEC60950-1 I/P-O/P: 3.75KVAC/min I/P-FG:2 KVAC/min O/P-FG:1.5KVAC/min	I/P-O/P: 4.125 KVAC/min I/P-FG: 2.4KVAC/min O/P-FG: 1.8 KVAC/min Ta:25°C	I/P-O/P: 5.54mA I/P-FG: 4.99mA O/P-FG: 5.77mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 27.7GΩ I/P-FG: 17.9G Ω O/P-FG: 30G Ω NO DAMAGE
3	GROUNDING CONTINUITY	IEC60950-1 FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40A / 2min Ta:25°C	26mΩ

### E.M.C TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS
2	CONDUCTION	EN55015 CLASS B	I/P: 230 VAC /50HZ O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab
3	RADIATION	EN55015 CLASS B	I/P: 230 VAC /50HZ O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare			



■ **RELIABILITY TEST**

**ENVIRONMENT TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																																																												
1	TEMPERATURE RISE TEST	MODEL : HLG-480H-48 1. ROOM AMBIENT BURN-IN : 2.5 HRS I/P : 230VAC O/P : FULL LOAD Ta= 29.4 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 63.8 °C																																																																																																														
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 29.4 °C</th> <th>HIGH AMBIENT Ta= 63.8 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD2</td><td>84.4°C</td><td>97.6°C</td></tr> <tr><td>2</td><td>C10</td><td>81.5°C</td><td>94.7°C</td></tr> <tr><td>3</td><td>Q1</td><td>82.4°C</td><td>95.6°C</td></tr> <tr><td>4</td><td>D8</td><td>84.6°C</td><td>97.6°C</td></tr> <tr><td>5</td><td>Q10</td><td>83.0°C</td><td>96.2°C</td></tr> <tr><td>6</td><td>Q12</td><td>83.7°C</td><td>96.9°C</td></tr> <tr><td>7</td><td>RY1</td><td>83.1°C</td><td>95.9°C</td></tr> <tr><td>8</td><td>ZNR2</td><td>77.8°C</td><td>89.2°C</td></tr> <tr><td>9</td><td>C1</td><td>76.8°C</td><td>88.2°C</td></tr> <tr><td>10</td><td>C5</td><td>77.8°C</td><td>89.8°C</td></tr> <tr><td>11</td><td>L3</td><td>83.0°C</td><td>96.5°C</td></tr> <tr><td>12</td><td>U1</td><td>78.4°C</td><td>89.9°C</td></tr> <tr><td>13</td><td>U2</td><td>79.1°C</td><td>91.1°C</td></tr> <tr><td>14</td><td>T1 Primary side</td><td>83.2°C</td><td>98.0°C</td></tr> <tr><td>15</td><td>T2 Primary side</td><td>85.1°C</td><td>99.2°C</td></tr> <tr><td>16</td><td>Q100</td><td>82.9°C</td><td>98.0°C</td></tr> <tr><td>17</td><td>Q121</td><td>83.0°C</td><td>98.2°C</td></tr> <tr><td>18</td><td>C115</td><td>77.6°C</td><td>91.8°C</td></tr> <tr><td>19</td><td>C117</td><td>75.1°C</td><td>89.2°C</td></tr> <tr><td>20</td><td>LF100</td><td>74.5°C</td><td>88.9°C</td></tr> <tr><td>21</td><td>T500</td><td>78.6°C</td><td>91.6°C</td></tr> <tr><td>22</td><td>C511</td><td>78.8°C</td><td>91.8°C</td></tr> <tr><td>23</td><td>U501</td><td>78.0°C</td><td>91.1°C</td></tr> <tr><td>24</td><td>J101</td><td>77.9°C</td><td>92.5°C</td></tr> <tr><td>25</td><td>RTH2</td><td>79.3°C</td><td>91.8°C</td></tr> <tr><td>26</td><td>C93</td><td>80.6°C</td><td>93.4°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 29.4 °C	HIGH AMBIENT Ta= 63.8 °C	1	BD2	84.4°C	97.6°C	2	C10	81.5°C	94.7°C	3	Q1	82.4°C	95.6°C	4	D8	84.6°C	97.6°C	5	Q10	83.0°C	96.2°C	6	Q12	83.7°C	96.9°C	7	RY1	83.1°C	95.9°C	8	ZNR2	77.8°C	89.2°C	9	C1	76.8°C	88.2°C	10	C5	77.8°C	89.8°C	11	L3	83.0°C	96.5°C	12	U1	78.4°C	89.9°C	13	U2	79.1°C	91.1°C	14	T1 Primary side	83.2°C	98.0°C	15	T2 Primary side	85.1°C	99.2°C	16	Q100	82.9°C	98.0°C	17	Q121	83.0°C	98.2°C	18	C115	77.6°C	91.8°C	19	C117	75.1°C	89.2°C	20	LF100	74.5°C	88.9°C	21	T500	78.6°C	91.6°C	22	C511	78.8°C	91.8°C	23	U501	78.0°C	91.1°C	24	J101	77.9°C	92.5°C	25	RTH2	79.3°C	91.8°C	26	C93	80.6°C	93.4°C
NO	Position	ROOM AMBIENT Ta= 29.4 °C	HIGH AMBIENT Ta= 63.8 °C																																																																																																													
1	BD2	84.4°C	97.6°C																																																																																																													
2	C10	81.5°C	94.7°C																																																																																																													
3	Q1	82.4°C	95.6°C																																																																																																													
4	D8	84.6°C	97.6°C																																																																																																													
5	Q10	83.0°C	96.2°C																																																																																																													
6	Q12	83.7°C	96.9°C																																																																																																													
7	RY1	83.1°C	95.9°C																																																																																																													
8	ZNR2	77.8°C	89.2°C																																																																																																													
9	C1	76.8°C	88.2°C																																																																																																													
10	C5	77.8°C	89.8°C																																																																																																													
11	L3	83.0°C	96.5°C																																																																																																													
12	U1	78.4°C	89.9°C																																																																																																													
13	U2	79.1°C	91.1°C																																																																																																													
14	T1 Primary side	83.2°C	98.0°C																																																																																																													
15	T2 Primary side	85.1°C	99.2°C																																																																																																													
16	Q100	82.9°C	98.0°C																																																																																																													
17	Q121	83.0°C	98.2°C																																																																																																													
18	C115	77.6°C	91.8°C																																																																																																													
19	C117	75.1°C	89.2°C																																																																																																													
20	LF100	74.5°C	88.9°C																																																																																																													
21	T500	78.6°C	91.6°C																																																																																																													
22	C511	78.8°C	91.8°C																																																																																																													
23	U501	78.0°C	91.1°C																																																																																																													
24	J101	77.9°C	92.5°C																																																																																																													
25	RTH2	79.3°C	91.8°C																																																																																																													
26	C93	80.6°C	93.4°C																																																																																																													
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 100 % LOAD Ta= -45 °C	TEST : OK																																																																																																												
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P : 315 VAC O/P : FULL LOAD Ta= 60°C HUMIDITY= 95 %R.H	TEST : OK																																																																																																												
4	TEMPERATURE COEFFICIENT	± 0.02 %/°C(0-60°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.004 %/°C(0-60°C)																																																																																																												

5	STORAGE TEMPERATURE TEST	<ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -50°C~ +125°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 100 CYCLE</li> <li>5. Input/Output condition : STATIC</li> </ol>	OK																														
6	THERMAL SHOCK TEST	<ol style="list-style-type: none"> <li>1. Thermal shock Temperature : -45°C~ +65°C</li> <li>2. Temperature change rate : 25°C / MIN</li> <li>3. Dwell time low and high temperature : 30 MIN/EACH</li> <li>4. Total test cycle : 16 CYCLE</li> <li>5. Input/Output condition : 15cycle:230V/ FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle:230V/ FULL LOAD Burn In Test</li> </ol>	OK																														
7	VIBRATION TEST	<ol style="list-style-type: none"> <li>1 Carton &amp; 1 Set</li> <li>(1) Waveform : Sine Wave</li> <li>(2) Frequency : 10-500Hz</li> <li>(3) Sweep Time : 12min/sweep cycle</li> <li>(4) Acceleration : 5G</li> <li>(5) Test Time : 72min in each axis (X.Y.Z)</li> <li>(6) Ta : 25°C</li> </ol>	TEST : OK																														
8	CAPACITOR LIFE CYCLE	<p>SUPPOSE C117 IS THE MOST CRITICAL COMPONENT</p> <ol style="list-style-type: none"> <li>(1) I/P : 230VAC O/P : FULL LOAD Ta= 25°C LIFE TIME</li> <li>(2) I/P : 230VAC O/P : FULL LOAD Ta= 60°C LIFE TIME</li> <li>(3) I/P : 230VAC O/P : 75% LOAD Ta= 60°C LIFE TIME</li> <li>(4) I/P : 230VAC O/P : 50% LOAD Ta= 60°C LIFE TIME</li> </ol>	<ol style="list-style-type: none"> <li>(1) 132638HRS</li> <li>(2) 47580HRS</li> <li>(3) 58920HRS</li> <li>(4) 89096HRS</li> </ol>																														
9	MTBF	<p>Conducted by Parts Stress Analysis Prediction 345.5K hrs min. Telcordia SR-332 (Bellcore) ; 95.3K hrs min. MIL-HDBK-217F (25°C)</p>																															
10	DMTBF/Accelerated Life Test	<p>Demonstration Mean Time Between Failure(Expected Life) : 62,000 hours @ Tcase75°C</p>  <table border="1"> <caption>Approximate data points from the Lifetime vs Temperature graph</caption> <thead> <tr> <th>Tcase (°C)</th> <th>Lifetime (K)</th> </tr> </thead> <tbody> <tr><td>25</td><td>100</td></tr> <tr><td>30</td><td>100</td></tr> <tr><td>35</td><td>100</td></tr> <tr><td>40</td><td>100</td></tr> <tr><td>45</td><td>100</td></tr> <tr><td>50</td><td>100</td></tr> <tr><td>55</td><td>100</td></tr> <tr><td>60</td><td>100</td></tr> <tr><td>65</td><td>100</td></tr> <tr><td>70</td><td>100</td></tr> <tr><td>75</td><td>70</td></tr> <tr><td>80</td><td>45</td></tr> <tr><td>85</td><td>30</td></tr> <tr><td>90</td><td>25</td></tr> </tbody> </table>		Tcase (°C)	Lifetime (K)	25	100	30	100	35	100	40	100	45	100	50	100	55	100	60	100	65	100	70	100	75	70	80	45	85	30	90	25
Tcase (°C)	Lifetime (K)																																
25	100																																
30	100																																
35	100																																
40	100																																
45	100																																
50	100																																
55	100																																
60	100																																
65	100																																
70	100																																
75	70																																
80	45																																
85	30																																
90	25																																

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT TSENG

12.10.30 A50-F031