

MODEL : APC-12-350

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 300 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 45 mVp-p (Max)	PASS
2	OUTPUT VOLTAGE TOLERANCE	V1: -5%~ +5% (Max)	I/P: 100VAC / 264 VAC O/P:FULL/ 0% LOAD Ta:25°C	V1: -0.05%~ 0.3 %	PASS
3	LINE REGULATION	V1: -1%~ +1% (Max)	I/P: 100 VAC ~ 264VAC O/P:FULL LOAD Ta:25°C	V1: -0.01%~ 0.03 %	PASS
4	LOAD REGULATION	V1: -3%~ +3% (Max)	I/P: 230 VAC O/P:FULL -MIN LOAD Ta:25°C	V1: -0.1%~ 0.3 %	PASS
5	SET UP TIME	230VAC/ 3000 ms (Max) 115VAC/ 3000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 868.557 ms 115 VAC/ 572.812ms	PASS
6	RISE TIME	230VAC/ 180 ms (Max) 115VAC/ 150 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 137.648 ms 115 VAC/ 121.365 ms	PASS
7	HOLD TIME	230VAC/ 20 ms (Typ) 115VAC/ 15 ms (Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 82.954 ms 115 VAC/ 18.886 ms	PASS
8	OVER/UNDERSHOOT TEST	< ±5 %	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: ±1.66%	PASS

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90 VAC~ 264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	90 V~ 264 V	PASS
			(1)I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%= 300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (2) I/P:230VAC ON: 0.5 Sec . OFF: 0.5 Sec 20MIN (AC POWER ON/OFF NO DAMAGE)	TEST: (1) OK (2) OK	

2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90 VAC ~264 VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	PASS
3	EFFICIENCY	82 % (Typ)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	83.14 %	PASS
4	INPUT CURRENT	230 V/ 0.2 A (Typ) 115 V/ 0.35 A (Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I =0.1474A/ 230VAC I =0.2463A/ 115VAC	PASS
5	INRUSH CURRENT	230 V/ 70 A Twidth =120 us measured at 50% Ipeak COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I =53.945 A Twidth = 102 us	PASS

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER VOLTAGE PROTECTION	CH1: 39.6 V~ 46.8 V	I/P: 264 VAC I/P: 230 VAC I/P: 90 VAC O/P:MIN LOAD Ta:25°C	42.864 V/264VAC 42.864 V/ 230VAC 42.864 V/ 90VAC Shut off O/P voltage, clamping by zener diode	PASS
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE Constant Current Limiting	PASS

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																																																						
1	TEMPERATURE RISE TEST	MODEL : APC-12-350 1. ROOM AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 32.3 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 45.1 °C			PASS																																																																						
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 32.3 °C</th> <th>HIGH AMBIENT Ta= 45.1 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>KBP208G</td><td>56.5°C</td><td>70.5°C</td></tr> <tr><td>2</td><td>L1</td><td>DRGZ001D</td><td>59.1°C</td><td>73.0°C</td></tr> <tr><td>3</td><td>C5</td><td>12uF/400V KM</td><td>53.6°C</td><td>67.4°C</td></tr> <tr><td>4</td><td>C6</td><td>12uF/400V KM</td><td>71.9°C</td><td>85.3°C</td></tr> <tr><td>5</td><td>D1</td><td>1N4007</td><td>81.5°C</td><td>94.5°C</td></tr> <tr><td>6</td><td>U1</td><td>SD4843</td><td>84.4°C</td><td>97.8°C</td></tr> <tr><td>7</td><td>C9</td><td>10uF/50V YXF</td><td>73.4°C</td><td>86.3°C</td></tr> <tr><td>8</td><td>T1</td><td>TF6318</td><td>72.2°C</td><td>84.8°C</td></tr> <tr><td>9</td><td>C2</td><td>22uF/50V KY</td><td>80.8°C</td><td>93.7°C</td></tr> <tr><td>10</td><td>D10</td><td>HER306</td><td>83.8°C</td><td>95.5°C</td></tr> <tr><td>11</td><td>C15</td><td>100uF/50V GL</td><td>62.8°C</td><td>75.3°C</td></tr> <tr><td>12</td><td>C16</td><td>47uF/50V GL</td><td>56.3°C</td><td>68.9°C</td></tr> <tr><td>13</td><td>C17</td><td>47uF/50V GL</td><td>71.1°C</td><td>83.6°C</td></tr> </tbody> </table>	NO	Position	P/N	ROOM AMBIENT Ta= 32.3 °C	HIGH AMBIENT Ta= 45.1 °C	1	BD1	KBP208G	56.5°C	70.5°C	2	L1	DRGZ001D	59.1°C	73.0°C	3	C5	12uF/400V KM	53.6°C	67.4°C	4	C6	12uF/400V KM	71.9°C	85.3°C	5	D1	1N4007	81.5°C	94.5°C	6	U1	SD4843	84.4°C	97.8°C	7	C9	10uF/50V YXF	73.4°C	86.3°C	8	T1	TF6318	72.2°C	84.8°C	9	C2	22uF/50V KY	80.8°C	93.7°C	10	D10	HER306	83.8°C	95.5°C	11	C15	100uF/50V GL	62.8°C	75.3°C	12	C16	47uF/50V GL	56.3°C	68.9°C	13	C17	47uF/50V GL	71.1°C	83.6°C	
NO	Position	P/N	ROOM AMBIENT Ta= 32.3 °C	HIGH AMBIENT Ta= 45.1 °C																																																																							
1	BD1	KBP208G	56.5°C	70.5°C																																																																							
2	L1	DRGZ001D	59.1°C	73.0°C																																																																							
3	C5	12uF/400V KM	53.6°C	67.4°C																																																																							
4	C6	12uF/400V KM	71.9°C	85.3°C																																																																							
5	D1	1N4007	81.5°C	94.5°C																																																																							
6	U1	SD4843	84.4°C	97.8°C																																																																							
7	C9	10uF/50V YXF	73.4°C	86.3°C																																																																							
8	T1	TF6318	72.2°C	84.8°C																																																																							
9	C2	22uF/50V KY	80.8°C	93.7°C																																																																							
10	D10	HER306	83.8°C	95.5°C																																																																							
11	C15	100uF/50V GL	62.8°C	75.3°C																																																																							
12	C16	47uF/50V GL	56.3°C	68.9°C																																																																							
13	C17	47uF/50V GL	71.1°C	83.6°C																																																																							

2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 264 VAC/100 VAC O/P: 100% LOAD Ta= -30 °C	TEST : OK	PASS
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 45 °C HUMIDITY= 95 %R.H	TEST : OK	PASS
4	TEMPERATURE COEFFICIENT	± 0.2 %(0-50°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.075 %(0-50°C)	PASS
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C ~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		TEST : OK	PASS
6.	THERMAL SHOCK TEST	1. Thermal shock Temperature : - 35 °C ~ + 50 °C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load 58SEC ON/2SEC OFF		TEST : OK	PASS
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	PASS
8	CAPACITOR LIFE CYCLE	APC-12-350: SUPPOSE C15 IS THE MOST CRITICAL COMPONENT (1) I/P: 230 VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 187624 HRS (2) I/P: 230 VAC O/P:FULL LOAD Ta= 45 °C LIFE TIME= 47892 HRS			PASS
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1145.7K HRS			PASS
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 20,000 hours @ Tcase 70°C , 50,000 hours @ Tcase 55°C			PASS

SAFETY TEST

1	WITHSTAND VOLTAGE	I/P-O/P: 3.75 KVAC/min EN 60950	I/P-O/P: 4.2 KVAC/min Ta:25°C	I/P-O/P: 1.883 mA NO DAMAGE	PASS
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: >9999 MΩ NO DAMAGE	PASS
3	LEAKAGE CURRENT	< 0.25 mA / 240VAC EN 60950	I/P: 264 VAC O/P:NO LOAD Ta:25°C	L-FG: 2.2 uA N-FG: 2.2 uA	PASS

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 220V/230V/240V AC 50HZ O/P:100%/75%/50%/25% LOAD Ta:25°C	PASS	PASS
2	CONDUCTION	EN55015	I/P:230 VAC (50HZ) /115V(60HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	PASS

3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V(60HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N :2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
7	Test by certified Lab & Test Report Prepare				

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U1 Rated SD4843 : 650 V 11 A	I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz Ta:25°C	(1)512V/1.42A (2)460V/1.29A (3)516V/520mA (4)540V/810mA (1)274V/660mA (2)158V/590mA (3)242V/430mA (4)286V/880mA	PASS
2	Diode Peak Voltage	D10 Rated HER306 : 600 V 3 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz Ta:25°C	(1)237 V (2) 203V (3) 234V (4) 238V (1) 39.6V (2) 41.6V (3) 36.0V (4)36.4 V	PASS



12W Single Output Switching Power Supply

APC-12 series

3	Input Capacitor Voltage	C 5 Rated CAPXON : 12 u / 400 V 105°C / KM Series	I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2)Min load input on /off (3)Burn-IN 1Hour Ta:25°C	(1) 398 V (2) 390 V (3) 388 V	PASS
4	Control IC Voltage Test	U 1 Rated SD4843 : 21 V	I/P:High-Line +3V = 267 V O/P:(1).Output Short (2).O.L.P (3).O.V.P. (4).NO LOAD LOW LINE Ta:25°C	(1) 16.2V (2) 16.2V (3) 16.2V (4) 12.3V	PASS

2007/11/26 A50-G058

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/11/1	RD SAMPLE	PASS	SKY	HOWAY
2011/6/10	PRODUCT SAMPLE (W1106A171)	PASS	SKY	HOWAY
2011/7/28	PRODUCT SAMPLE (W1107G151)	PASS	SKY	HOWAY