



Test Report: NPB-120-12

120W Compact Size and Wide Output Range Charger

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	BOOST CHARGE VOLTAGE	14.4V± 0.3 V	I/P: 230 VAC O/P: 90% LOAD Ta:25°C	14.42V
2	FLOAT CHARGE VOLTAGE	13.8V± 0.3 V	I/P: 230 VAC O/P:NO LOAD Ta:25°C	13.82V
3	OUTPUT CURRENT	6.8A±3%	I/P: 230 VAC O/P:C.V MODE-1V Ta:25°C	6.81A
4	LEAKAGE CURRENT FROM BATTERY (TYP)	<1mA	I/P: AC OFF O/P:BAT. LOAD Ta:25°C	0.055mA
5	VOLTAGE ADJUSTABLE RANGE	10.5~15.2V	I/P: 230 VAC O/P: 90% LOAD Ta:25°C	9.66V~15.92V
6	CURRENT ADJUSTABLE RANGE	50%~100%	I/P: 230 VAC O/P:C.V MODE-1V Ta:25°C	48.1%~112.3%

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~264VAC 127VDC~370VDC	(1) I/P:TESTING O/P:FULL LOAD (2) I/P:DC TESTING(L:+ N:-) O/P: FULL / 50% LOAD (3) I/P:DC TESTING(L:- N:+) O/P: FULL / 50% LOAD Ta:25°C	(1) 75.6V~264V (2) 105.81Vdc~370Vdc/FULL LOAD 105.8Vdc~370Vdc/50% LOAD (3) 105.89Vdc~370Vdc/FULL LOAD 105.81Vdc~370Vdc/50% LOAD
			I/P: LOW-LINE-3V=87 V HIGH-LINE+ 15%= 300 V O/P:BAT. LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK
3	INPUT CURRENT (TYP)	230 V/ 0.8 A 115 V/ 1.5 A	I/P: 230 VAC I/P: 115 VAC O/P:BAT. LOAD Ta:25°C	I =0.537A/ 230VAC I =1.037A/ 115VAC

4	POWER FACTOR (TYP)	0.92/ 230 VAC 0.98/ 115 VAC	I/P: 230 VAC I/P: 115 VAC O/P:BAT. LOAD Ta:25°C	0.926/ 230VAC 0.984/ 115VAC
5	EFFICIENCY (TYP)	87%	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	88.29 %
6	INRUSH CURRENT (TYP)	230 V/ 55 A COLD START	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	I =51.2A/ 230VAC
<p>INPUT=230VAC/50HZ @ FULL LOAD CH2 : AC Input Voltage CH4 : Input current (1V=1A)</p>				
7	GAIN-PHASE MARGIN TEST	GAIN MARGIN < -10dB PHASE MARGIN > =60 <u>Gain Curve slope:</u> -10dB/dec~-40dB/dec	(1) CV MODE(MAX) /264Vac (2) CV MODE(MAX)/100Vac (3) CV MODE(Min)/264Vac (4) CV MODE(Min)/100Vac Ta:25°C	(1)96.782 ° /-16.858dB/ -14.5dB/dec (2)96.724 ° /-17.091dB/ -13.2dB/dec (3)112.081 ° /-14.717dB/ -15.2dB/dec (4)112.72 ° /-14.833dB/ -10.1dB/dec
8	NO LOAD POWER CONSUMPTION	230V/0.15W	I/P: 230 VAC O/P:NO LOAD (AC S.W OFF) Ta:25°C	0.057 W

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER VOLTAGE PROTECTION	CH1: 16 ~ 20V PROTECTION RESULT Shut down and latch off o/p voltage, re-power on to recover	I/P: 264 VAC I/P: 90 VAC O/P:TESTING Ta:25°C	18.5V/ 264VAC 18.5V/ 90VAC PROTECTION TYPE : Shut down and latch off o/p voltage, re-power on to recover

2	OVER TEMPERATURE PROTECTION	SPEC: NO DAMAGE Hiccup, recovers automatically after temperature goes down	I/P: 264 VAC I/P: 90 VAC O/P:BAT. LOAD	O.T.P. Active PROTECTION TYPE : Hiccup, recovers automatically after temperature goes down
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE Constant current limiting, charger will shut down after 5 sec, re-power on to recover	I/P: 264 VAC O/P: BAT. LOAD Ta:25°C	NO DAMAGE PROTECTION TYPE : Constant current limiting, charger will shut down after 5 sec, re-power on to recover
4	BATTERY REVERSE POLARITY	By internal fuse open	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	By internal fuse open
5	FLOW BACKWARD PROTECTION	BATTERY VOLTAGE : ≤18V	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	NO DAMAGE

CONTROL FUNCTION TEST

N O	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT												
1	CHARGE CURE	<p>I/P:230Vac O/P:TESTING Ta:25°C</p> <p>☉ Default 2 stage charging curve</p> <table border="1"> <thead> <tr> <th>Item</th> <th>Specification</th> <th>Result</th> <th>Item</th> <th>Specification</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>Charge Voltage</td> <td>100% CC</td> <td>Pass</td> <td>Charge Current</td> <td>10% CC</td> <td>Pass</td> </tr> </tbody> </table> <p>☉ Default 3 stage charging curve</p> <p>Color of LED Loading Indicator: stage 1 (Red), stage 2 (Green), stage 3 (Green)</p>	Item	Specification	Result	Item	Specification	Result	Charge Voltage	100% CC	Pass	Charge Current	10% CC	Pass	<p>I/P:230Vac O/P:TESTING Ta:25°C</p>	<p>Pass</p>
Item	Specification	Result	Item	Specification	Result											
Charge Voltage	100% CC	Pass	Charge Current	10% CC	Pass											

2.	LED INDICATOR				
		LED	Description	TEST : <u>OK</u>	
		Green	FLOATING/FULLY		
		Red	Charging (stage 1 or stage 2)		
		Light off	OVP /OUTPUT SHORT/OLP		
		Green Flash	OTP		
		I/P: 230V O/P: TESTING LOAD Ta:25°C			

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 5/Q6 Rated : 600 V / 11A	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT Ta:25°C	Q5 VDS : (1) 467V (2) 463V (3) 447V (4) 503V Q6 VDS : (1) 479V (2) 479V (3) 467V (4) 487V
2	P.F.C Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : 600V / 13A	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT Ta:25°C	VDS : (1) 476V (2) 468V (3) 400V (4) 444V
3	P.F.C DIODE	D 4 Rated : 9A/ 600V	AC ON/OFF I/P:High-Line +3V =267 V O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT Ta:25°C	(1) 512V (2) 504V (3) 468V (4) 512V
4	Transistor Peak Voltage	Q210/Q211 Rated : 60 V / 80A	AC ON/OFF I/P:Low-Line -3V = 267 V O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT	Q210 VDS : (1) 37.2V (2) 33.6V (3) 35.6V (4) 39.6V Q211 VDS : (1) 41.6V (2) 38.0V (3) 38.8V (4) 42.8V
5	Input Capacitor Voltage	C 5 Rated : 82 u / 420 V	I/P:High-Line +3V =267 V O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT Ta:25°C	(1) 416V (2) 412V (3) 402V (4) 408V

6	Control IC Voltage Test	PWM IC U1 Rated 10V~20V	AC ON/OFF I/P:High-Line +3V =267 V O/P: (1)CV(max) (2)CV(min) (3)no load (4)OUTPUT SHORT Ta:25°C	U1	U102
		PFC IC U2 Rated 9.75V~20V		(1) 15.8V (2) 15.8V (3) 15.8V (4) 15.8V	(1) 12.6V (2) 12.6V (3) 12.6V (4) 12.6V
		O/P IC U102 Rated 3V~30V		U2 (1) 15.2V (2) 15.2V (3) 15.2V (4) 15.2V	

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC I/P-FG:2 KVAC O/P-FG:0.5KVAC	I/P-O/P: 3.6 KVAC I/P-FG: 1.8 KVAC O/P-FG: 0.6 KVAC Ta:25°C	I/P-O/P: 2.604 mA I/P-FG: 2.515 mA O/P-FG: 1.880 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 600 VDC I/P-FG: 600 VDC O/P-FG: 600 VDC Ta:25°C	I/P-O/P: 10G Ω I/P-FG: 10 GΩ O/P-FG 10G Ω NO DAMAGE

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	BS EN/EN61000-3-2 CLASS A	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	■ PASS
2	CONDUCTION	BS EN/EN55032(CISPR32) EN/EN55014-1 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	■ PASS Test by certified Lab
3	RADIATION	BS EN/EN55032(CISPR32) EN/EN55014-1 CLASS B	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	■ PASS Test by certified Lab
4	E.S.D	BS EN/EN61000-4-2 AIR : 8KV / Contact : 4KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	■ CRITERIA A □ CRITERIA B
5	E.F.T	BS EN/EN61000-4-4 INPUT: 1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	■ CRITERIA A □ CRITERIA B
6	SURGE	BS EN/EN 61000-4-5 L-N :1KV L,N-PE:2KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	■ CRITERIA A □ CRITERIA B
7	Test by certified Lab & Test Report Prepare Any contradictions of the test results, please refer to the latest EMC test report			

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																																																																																				
1	TEMPERATURE RISE TEST	MODEL : NPB-120-12 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 21.3 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 45.8 °C																																																																																																																																						
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 21.3 °C</th> <th>HIGH AMBIENT Ta= 45.8 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>RTH1</td><td>64.9°C</td><td>82.7°C</td></tr> <tr><td>2</td><td>RTH2</td><td>54.6°C</td><td>80.3°C</td></tr> <tr><td>3</td><td>ZNR1</td><td>46.3°C</td><td>70.1°C</td></tr> <tr><td>4</td><td>LF1</td><td>40.9°C</td><td>65.9°C</td></tr> <tr><td>5</td><td>LF2</td><td>51.1°C</td><td>76.0°C</td></tr> <tr><td>6</td><td>C2</td><td>50.8°C</td><td>77.6°C</td></tr> <tr><td>7</td><td>L1</td><td>75.9°C</td><td>104.9°C</td></tr> <tr><td>8</td><td>C5</td><td>57.7°C</td><td>84.5°C</td></tr> <tr><td>9</td><td>BD1</td><td>56.1°C</td><td>81.4°C</td></tr> <tr><td>10</td><td>C6</td><td>54.4°C</td><td>80.5°C</td></tr> <tr><td>11</td><td>Q1</td><td>43.6°C</td><td>69.0°C</td></tr> <tr><td>12</td><td>D4</td><td>40.8°C</td><td>66.1°C</td></tr> <tr><td>13</td><td>Q6</td><td>40.9°C</td><td>66.6°C</td></tr> <tr><td>14</td><td>U2</td><td>52.2°C</td><td>89.9°C</td></tr> <tr><td>15</td><td>U1</td><td>57.7°C</td><td>83.8°C</td></tr> <tr><td>16</td><td>Q15</td><td>60.7°C</td><td>89.3°C</td></tr> <tr><td>17</td><td>T1coil</td><td>64.9°C</td><td>91.7°C</td></tr> <tr><td>18</td><td>C14</td><td>53.4°C</td><td>79.1°C</td></tr> <tr><td>19</td><td>T1core</td><td>61.7°C</td><td>88.2°C</td></tr> <tr><td>20</td><td>Q210</td><td>45.8°C</td><td>71.1°C</td></tr> <tr><td>21</td><td>Q215</td><td>44.8°C</td><td>70.1°C</td></tr> <tr><td>22</td><td>U100</td><td>56.6°C</td><td>82.8°C</td></tr> <tr><td>23</td><td>LF100</td><td>49.3°C</td><td>74.5°C</td></tr> <tr><td>24</td><td>C101</td><td>58.8°C</td><td>84.7°C</td></tr> <tr><td>25</td><td>Q201</td><td>61.0°C</td><td>86.0°C</td></tr> <tr><td>26</td><td>U110</td><td>49.8°C</td><td>74.3°C</td></tr> <tr><td>27</td><td>D100</td><td>51.9°C</td><td>77.2°C</td></tr> <tr><td>28</td><td>C104</td><td>50.9°C</td><td>76.0°C</td></tr> <tr><td>29</td><td>J101</td><td>64.2°C</td><td>89.4°C</td></tr> <tr><td>30</td><td>R105</td><td>49.3°C</td><td>74.9°C</td></tr> <tr><td>31</td><td>D104</td><td>51.0°C</td><td>76.5°C</td></tr> <tr><td>32</td><td>PCB</td><td>51.4°C</td><td>76.9°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 21.3 °C	HIGH AMBIENT Ta= 45.8 °C	1	RTH1	64.9°C	82.7°C	2	RTH2	54.6°C	80.3°C	3	ZNR1	46.3°C	70.1°C	4	LF1	40.9°C	65.9°C	5	LF2	51.1°C	76.0°C	6	C2	50.8°C	77.6°C	7	L1	75.9°C	104.9°C	8	C5	57.7°C	84.5°C	9	BD1	56.1°C	81.4°C	10	C6	54.4°C	80.5°C	11	Q1	43.6°C	69.0°C	12	D4	40.8°C	66.1°C	13	Q6	40.9°C	66.6°C	14	U2	52.2°C	89.9°C	15	U1	57.7°C	83.8°C	16	Q15	60.7°C	89.3°C	17	T1coil	64.9°C	91.7°C	18	C14	53.4°C	79.1°C	19	T1core	61.7°C	88.2°C	20	Q210	45.8°C	71.1°C	21	Q215	44.8°C	70.1°C	22	U100	56.6°C	82.8°C	23	LF100	49.3°C	74.5°C	24	C101	58.8°C	84.7°C	25	Q201	61.0°C	86.0°C	26	U110	49.8°C	74.3°C	27	D100	51.9°C	77.2°C	28	C104	50.9°C	76.0°C	29	J101	64.2°C	89.4°C	30	R105	49.3°C	74.9°C	31	D104	51.0°C	76.5°C	32	PCB	51.4°C	76.9°C
NO	Position	ROOM AMBIENT Ta= 21.3 °C	HIGH AMBIENT Ta= 45.8 °C																																																																																																																																					
1	RTH1	64.9°C	82.7°C																																																																																																																																					
2	RTH2	54.6°C	80.3°C																																																																																																																																					
3	ZNR1	46.3°C	70.1°C																																																																																																																																					
4	LF1	40.9°C	65.9°C																																																																																																																																					
5	LF2	51.1°C	76.0°C																																																																																																																																					
6	C2	50.8°C	77.6°C																																																																																																																																					
7	L1	75.9°C	104.9°C																																																																																																																																					
8	C5	57.7°C	84.5°C																																																																																																																																					
9	BD1	56.1°C	81.4°C																																																																																																																																					
10	C6	54.4°C	80.5°C																																																																																																																																					
11	Q1	43.6°C	69.0°C																																																																																																																																					
12	D4	40.8°C	66.1°C																																																																																																																																					
13	Q6	40.9°C	66.6°C																																																																																																																																					
14	U2	52.2°C	89.9°C																																																																																																																																					
15	U1	57.7°C	83.8°C																																																																																																																																					
16	Q15	60.7°C	89.3°C																																																																																																																																					
17	T1coil	64.9°C	91.7°C																																																																																																																																					
18	C14	53.4°C	79.1°C																																																																																																																																					
19	T1core	61.7°C	88.2°C																																																																																																																																					
20	Q210	45.8°C	71.1°C																																																																																																																																					
21	Q215	44.8°C	70.1°C																																																																																																																																					
22	U100	56.6°C	82.8°C																																																																																																																																					
23	LF100	49.3°C	74.5°C																																																																																																																																					
24	C101	58.8°C	84.7°C																																																																																																																																					
25	Q201	61.0°C	86.0°C																																																																																																																																					
26	U110	49.8°C	74.3°C																																																																																																																																					
27	D100	51.9°C	77.2°C																																																																																																																																					
28	C104	50.9°C	76.0°C																																																																																																																																					
29	J101	64.2°C	89.4°C																																																																																																																																					
30	R105	49.3°C	74.9°C																																																																																																																																					
31	D104	51.0°C	76.5°C																																																																																																																																					
32	PCB	51.4°C	76.9°C																																																																																																																																					

2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : CV-1 Ta= -35°C	TEST : OK
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 45°C HUMIDITY= 95 %R.H	TEST : OK
4	TEMPERATURE COEFFICIENT	± 0.05 %/ (0°C~45°C)	I/P : 230 VAC O/P : FULL LOAD	±0.0072 %/°C(0~45°C)
5	STORAGE TEMPERATURE TEST	-40~85°C	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10CYCLE 5. Input/Output condition : STATIC	
6	THERMAL SHOCK TEST	-30~45°C	1. Thermal shock Temperature : -35°C~ +50°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 15cycle:230V/ FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle:230V/ FULL LOAD Burn In Test	
7	VIBRATION TEST	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 3G (5) Test Time : 180min in each axis (X.Y.Z) (6) Ta : 25°C	
8	CAPACITOR LIFE CYCLE	SUPPOSE C101 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 45 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 45 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 45 °C LIFE TIME	(1) 266741.6HRS (2) 60518.3HRS (3) 81363.7HRS (4) 128208.2HRS	
9	MTBF	Conducted by Parts Stress Analysis Prediction 631.8K hrs min. Telcordia TR/SR-332 (Bellcore) ; 225.8K hrs min. MIL-HDBK-217F (25°C)		
10	Ongoing Reliability Test	I/P : 230VAC O/P : 80% LOAD TA=50°C Demonstration Mean Time Between Failure : 30,000 hours		

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		WANGDZ

2020.10.01 TAG-QA-009