



# Test Report: DDR-15G-3.3

---

15W DIN Rail Type DC-DC Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST


ENVIRONMENT TEST

## DESIGN VERIFY TEST

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE ADJUST RANGE	CH1:3.0 V~3.6 V	I/P : 24 VDC O/P : MIN LOAD Ta : 25°C	2.91V~3.73V
2	OUTPUT VOLTAGE TOLERANCE (Max)	V1: -2%~ 2%	I/P:9 VDC / 36VDC O/P:FULL/ MIN. LOAD Ta:25°C	V1: -1.03 %~0.98%
3	LINE REGULATION (Max)	V1:-0.5%~ 0.5%	I/P: 9VDC /36VDC O/P:FULL LOAD Ta:25°C	V1: -0.04 %~ 0.07%
4	LOAD REGULATION (Max)	V1: -1.5%~ 1.5%	I/P: 24VDC O/P:FULL ~MIN LOAD Ta:25°C	V1: -1.03 %~0.98%
5	OVER/UNDERSHOOT TEST	< ±15%	I/P:24VDC O/P:FULL LOAD Ta:25°C	TEST:4.4%
6	RIPPLE & NOISE (Max)	V1: 50 mVp-p	I/P: 24VDC O/P:FULL LOAD Ta:25°C	V1: 19 mVp-p

high frequency :







low frequency :



7	SET UP TIME (Max)	24VDC/120 ms	I/P:24 VDC O/P:FULL LOAD Ta:25°C	24VDC/ 25.8 ms
---	-------------------	--------------	--	----------------

INPUT=24VDC@ FULL LOAD




8	RISE TIME (Max)	24VDC/ 85 ms	I/P: 24 VDC O/P:FULL LOAD Ta:25°C	24VDC/8.754 ms
<p>INPUT=24VDC@ FULL LOAD</p> 				
9	HOLD UP TIME (TYP)	24VDC/8ms	I/P: 24VDC O/P:FULL LOAD Ta:25°C	24VDC/17.4 ms
<p>INPUT=24VDC @ FULL LOAD</p> 				
10	DYNAMIC LOAD	V1: 990 mVp-p	I/P: 24VDC O/P: (1)FULL /MIN LOAD 50%DUTY / 120HZ (2)FULL /MIN LOAD 50%DUTY / 1KHZ Ta:25°C	563mVp-p 503 mVp-p
<p>FULL /MIN LOAD 50%DUTY / 120HZ</p>  <p>FULL /MIN LOAD 50%DUTY / 1KHZ</p> 				

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	9VDC~ 36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	7.63V~ 36V

			I/P: LOW-LINE-0.2=8.8V HIGH-LINE+3V=39V O/P:FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN ( POWER ON/OFF NO DAMAGE )	TEST(1) <u>OK</u> (2) <u>OK</u> (3) <u>OK</u>
2	INPUT CURRENT(TYP)	24VDC/0.8 A	I/P: 24VDC O/P:FULL LOAD Ta:25°C	I =0.56A/24VDC
3	EFFICIENCY(TYP)	84%	I/P: 24VDC O/P:FULL LOAD Ta:25°C	84.13%

EFFICIENCY vs LOAD



4	INRUSH CURRENT(TYP)	24VDC/ 15 A COLD START	I/P: 24VDC O/P:FULL LOAD Ta:25°C	I =9.0A/ 24VDC
---	---------------------	---------------------------	--	----------------

INPUT=24VDC @ FULL LOAD



### PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	110%~150%RATED OUTPUT POWER	I/P: 36VDC I/P: 24 VDC I/P: 9 VDC O/P:TESTING Ta:25°C	131.4%/36VDC 133.1%/24VDC 131.4%/9VDC PROTECTION TYPE : Hiccup mode ,recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH: 3.8 V~4.7V	I/P: 36VDC I/P: 24 VDC I/P: 9 VDC O/P:MIN LOAD Ta:25°C	4.04V/36VDC 4.04V/ 24VDC 4.04V/ 9VDC PROTECTION TYPE : Shut down O/P voltage,re-power on to recover



3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 36VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE PROTECTION TYPE : Hiccup mode ,recovers automatically after fault condition is removed
4	INPUT REVERSE	POWER OK	I/P: 36VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE

**COMPONENT STRESS TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor ( D to S) or (C to E) Peak Voltage	Q 3 Rated : 100V	I/P:High-Line +3V =39V DC ON/OFF VDS: O/P: (1)Full Load (2)Output Short (3)full load continue Ta:25°C	VDS: (1)81.3V (2)78.9V (3) 85.3V
2	Diode Peak Voltage	Q100 Rated : 60V	I/P:High-Line +3V =39 V DC ON/OFF O/P: (1)Full Load (2)Output Short (3) full load continue Ta:25°C	VDS: (1)16.5V (2)15.3V (3)16.5V
3	Input Capacitor Voltage	C4 Rated: : 330 $\mu$ / 50V	I/P:High-Line +3V =39 V O/P: (1)Full Load input on/off (2) Min load input on /Off (3)Full Load /Min load Change (4)Full load continue Ta:25°C	C4: (1)41.4V (2)40.2V (3)40.2V (4)40.2V
4	Control IC Voltage Test	PWM IC U1 Rated -0.3V~30V  U100 Rated -0.3V~38V	I/P:High-Line +3V =39 V DC ON/OFF O/P:(1)FULL LOAD (2) Output Short (3)O.L.P (4)O.V.P. Ta:25°C	U1: (1) 18.1V (2) 9.7V (3) 18.1V (4) 10.5V U100 (1)15.3V (2)12.1V (3)15.3V (4)15.7V
5	Clamp Diode Peak Voltage	D3 Rated : 400V	I/P : High-Line +3V =39 V DC ON/OFF O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	D3: (1)55.4V (2)55.4V

**SAFETY TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	EN 60950-1 I/P-O/P:4KVDC/min	I/P-O/P: 4.4KVDC/min  Ta:25°C	I/P-O/P: 0 mA  NO DAMAGE



2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ NO DAMAGE
---	----------------------	----------------------	-----------------------------	------------------------------

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RADIATION	<input checked="" type="checkbox"/> EN55032 <input type="checkbox"/> EN55011 <input type="checkbox"/> CLASS A <input checked="" type="checkbox"/> CLASS B	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL Test by certified Lab
2	CONDUCTION	<input checked="" type="checkbox"/> EN55032 <input type="checkbox"/> EN55011 <input type="checkbox"/> CLASS A <input checked="" type="checkbox"/> CLASS B	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL Test by certified Lab
3	E.S.D	EN61000-4-2 <input type="checkbox"/> Din rail Model : AIR: 8KV / Contact: 6KV	I/P: 24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
4	E.F.T	EN61000-4-4 <input type="checkbox"/> INDUSTRY INPUT: 2KV	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
5	SURGE	IEC61000-4-5 <input type="checkbox"/> INDUSTRY line-line :1KV	I/P:24VDC O/P:FULL LOAD Ta:25°C	<input checked="" type="checkbox"/> CRITERIA A <input type="checkbox"/> CRITERIA B
6	Test by certified Lab & Test Report Prepare			

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																
1	TEMPERATURE RISE TEST	MODEL : DDR-15G-5 1. ROOM AMBIENT BURN-IN : 1 HRS I/P : 24VDC O/P : FULL LOAD Ta= 22.2 °C 2. HIGH AMBIENT BURN-IN : 1 HRS I/P : 24VDC O/P : FULL LOAD Ta= 60.8 °C																																																																		
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 22.2 °C</th> <th>HIGH AMBIENT Ta= 60.8 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>43.8°C</td><td>81.7°C</td></tr> <tr><td>2</td><td>LF100</td><td>62.6°C</td><td>98.4°C</td></tr> <tr><td>3</td><td>T1</td><td>65.4°C</td><td>100.8°C</td></tr> <tr><td>4</td><td>Q2</td><td>33.2°C</td><td>70.8°C</td></tr> <tr><td>5</td><td>Q100</td><td>62.5°C</td><td>97.7°C</td></tr> <tr><td>6</td><td>Q3</td><td>60.4°C</td><td>97.5°C</td></tr> <tr><td>7</td><td>D3</td><td>62.0°C</td><td>98.2°C</td></tr> <tr><td>8</td><td>U1</td><td>49.1°C</td><td>85.4°C</td></tr> <tr><td>9</td><td>C2</td><td>40.7°C</td><td>78.6°C</td></tr> <tr><td>10</td><td>C3</td><td>52.4°C</td><td>89.1°C</td></tr> <tr><td>11</td><td>C31</td><td>50.2°C</td><td>86.8°C</td></tr> <tr><td>12</td><td>C101</td><td>61.5°C</td><td>97.4°C</td></tr> <tr><td>13</td><td>C104</td><td>46.1°C</td><td>82.1°C</td></tr> <tr><td>14</td><td>C5</td><td>60.5°C</td><td>96.4°C</td></tr> <tr><td>15</td><td>R12</td><td>60.8°C</td><td>96.6°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 22.2 °C	HIGH AMBIENT Ta= 60.8 °C	1	LF1	43.8°C	81.7°C	2	LF100	62.6°C	98.4°C	3	T1	65.4°C	100.8°C	4	Q2	33.2°C	70.8°C	5	Q100	62.5°C	97.7°C	6	Q3	60.4°C	97.5°C	7	D3	62.0°C	98.2°C	8	U1	49.1°C	85.4°C	9	C2	40.7°C	78.6°C	10	C3	52.4°C	89.1°C	11	C31	50.2°C	86.8°C	12	C101	61.5°C	97.4°C	13	C104	46.1°C	82.1°C	14	C5	60.5°C	96.4°C	15	R12	60.8°C	96.6°C
NO	Position	ROOM AMBIENT Ta= 22.2 °C	HIGH AMBIENT Ta= 60.8 °C																																																																	
1	LF1	43.8°C	81.7°C																																																																	
2	LF100	62.6°C	98.4°C																																																																	
3	T1	65.4°C	100.8°C																																																																	
4	Q2	33.2°C	70.8°C																																																																	
5	Q100	62.5°C	97.7°C																																																																	
6	Q3	60.4°C	97.5°C																																																																	
7	D3	62.0°C	98.2°C																																																																	
8	U1	49.1°C	85.4°C																																																																	
9	C2	40.7°C	78.6°C																																																																	
10	C3	52.4°C	89.1°C																																																																	
11	C31	50.2°C	86.8°C																																																																	
12	C101	61.5°C	97.4°C																																																																	
13	C104	46.1°C	82.1°C																																																																	
14	C5	60.5°C	96.4°C																																																																	
15	R12	60.8°C	96.6°C																																																																	



# 15W DIN Rail Type DC-DC Converter

# DDR-15G series

2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P : 24 VDC O/P : 140 % LOAD Ta : 25°C	TEST : OK												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 12 VDC/ 36 VDC O/P : 100 % LOAD Ta= -45 °C	TEST : OK												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P : 39 VDC O/P : FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST: OK												
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~60°C)	I/P : 24 VDC O/P : FULL LOAD	± 0.01%(0~60°C)												
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : STATIC		TEST : OK												
7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 24VDC/Full Load DC ON/OFF TEST turn on 3sec ; turn off 1sec@15cycle\ 24VDC/Full Load DC ON@1cycle		TEST : OK												
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 3G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C  2 Din Rail <table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>Displacement</th> <th>Acceleration</th> </tr> </thead> <tbody> <tr> <td>2 (+3/-0) Hz up to 15Hz</td> <td>±2.5mm</td> <td>-----</td> </tr> <tr> <td>15Hz up to 50Hz</td> <td>-----</td> <td>2.3g</td> </tr> <tr> <td>Sweep rate</td> <td colspan="2">Max 1 Octave/minute</td> </tr> </tbody> </table>			Displacement	Acceleration	2 (+3/-0) Hz up to 15Hz	±2.5mm	-----	15Hz up to 50Hz	-----	2.3g	Sweep rate	Max 1 Octave/minute		TEST : OK
	Displacement	Acceleration														
2 (+3/-0) Hz up to 15Hz	±2.5mm	-----														
15Hz up to 50Hz	-----	2.3g														
Sweep rate	Max 1 Octave/minute															
9	CAPACITOR LIFE CYCLE	SUPPOSE C101 IS THE MOST CRITICAL COMPONENT (1) I/P : 24VDC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 24VDC O/P : FULL LOAD Ta= 60 °C LIFE TIME (3) I/P : 24VDC O/P : 75% LOAD Ta= 60 °C LIFE TIME (4) I/P : 24VDC O/P : 50% LOAD Ta= 60 °C LIFE TIME		(1) 632472.0HRS (2) 50194.8HRS (3) 70956.0HRS (4) 632472.0HRS												
10	MTBF	Conducted by Parts Stress Analysis Prediction 907K hrs min. MIL-HDBK-217F (25°C)														
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 60°C														

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		WANGDZ

12.10.30 A50-F031